



Ref. Certif. No.

SG ITS-32956M2

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Jackery Explorer 2000 Plus (power station)
Name and address of the applicant	Jackery Technology GmbH Adlerstr. 72, 40211 Düsseldorf, Germany
Name and address of the manufacturer	Shenzhen Hello Tech Energy Co., Ltd. Floor 1-5 of Building 4, Floor 2,3,4 and 5 of Building 7, Jia'anda Industrial Zone, East of Huafan Road, Tongsheng Community, Dalang Sub-District, Longhua area, 518109, Shenzhen, Guangdong, China
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	Shenzhen Hello Tech Energy Co., Ltd. Floor 1-5 of Building 4, Floor 2,3,4 and 5 of Building 7, Jia'anda Industrial Zone, East of Huafan Road, Tongsheng Community, Dalang Sub-District, Longhua area, 518109, Shenzhen, Guangdong, China
Ratings and principal characteristics	See page 2
Trademark (if any)	Jackery
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	JE-2000C
Additional information (if necessary may also be reported on page 2)	This certificate replaces CB Certificate No. SG ITS-32956M1 dated 09 April 2024 due to add national differences for Korea, update label, change the address of applicant and manufacturer and update table 4.1.2. Group and national differences for CENELEC countries (EN IEC 62368-1:2020 + A11:2020) and national differences for Korea have been considered.
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	230423064GZU-001 Modification 2

This CB Test Certificate is issued by the National Certification Body

Intertek Testing Services (Singapore) Pte Ltd
5, Pereira Road, #06-01
Asiawide Industrial Building
Singapore 368025



Date: 26 December 2024

Signature:

Ong Keng Chuan



Ref. Certif. No.

SG ITS-32956M2

Ratings and principal characteristics

Capacity:

Lithium-ion 45.6Ah / 44.8VDC (2042.8Wh)

DC input:

2 x DC 8mm Ports: 11-17.5V (Working Voltage) DC, 8A Max, Double to 8A Max,
17.5-60V (Working Voltage) DC, 12A Max, Double to 24A/1400W Max,

Charge mode AC input:

230V~, 50Hz, 10A Max, Class I (220V~, 60Hz, 10A Max, Class I for Korea market)

AC Outputs:

3 x AC Output: 230V~, 50Hz, 13A Max (220V~, 60Hz, 13A Max, for Korea market)

Total AC Output: 3000W Max, 6000W surge peak

2 x USB-C: 100W Max, 5VDC/3A, 9VDC/3A, 12VDC/3A, 15VDC/3A, 20VDC/5A

2 x USB-A: Quick Charge 3.0, 18W Max, 5-6VDC/3A, 6-9VDC/2A, 9-12VDC/1.5A

1 x DC Expansion Port: 32.2V-50.4VDC, 97A Max

1 x Car port: 12VDC, 10A Max

Date: 26 December 2024

Signature:

Ong Keng Chuan