




| | |
|--|---|
| TEST REPORT IEC 62368-1 Audio/video, information and communication technology equipment Part 1: Safety requirements | |
| Report Number | CTB25020704401RS01 |
| Date of issue | Feb. 24, 2025 |
| Total number of pages | 77 |
| Testing laboratory | |
| Name | Shenzhen CTB Testing Technology Co., Ltd. |
| Address | 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China |
| Applicant's name | |
| | Creature Information(Guangzhou)Technology Co., Limited |
| Address | Room 404-05, No.4, Nengyuan Rd., Tianhe District, Guangzhou, China |
| Test specification: | |
| Standard | EN IEC 62368-1:2020+A11:2020 |
| Test procedure | Safety report |
| Non-standard test method | N/A |
| TRF template used | |
| | IECEE OD-2020-F1:2021, Ed.1.4 |
| Test Report Form No | IEC62368_1E |
| Test Report Form(s) Originator | UL(US) |
| Master TRF | Dated 2022-04-14 |
| Copyright © 2022 IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE System). All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. | |
| Note: | |
| If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "★" indicates the testing items were fulfilled by subcontracted lab. "※" indicates the items are not in CNAS accreditation scope. | |

| | |
|-------------------------------------|--|
| Test item description: | Tablet PC(Notebook) |
| Trademark(s): | N/A |
| Manufacturer: | Creature Information(Guangzhou)Technology Co., Limited |
| Address: | Room 404-05, No.4, Nengyuan Rd., Tianhe District, Guangzhou, China |
| Model/Type reference: | MB02 (Additional models refer to see page 5) |
| Ratings: | 5V---2.0A Battery Capacity: 3.85Vdc, 8000mAh, 30.8Wh |

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):

| | | | |
|---|----------------------------|---|--|
| <input checked="" type="checkbox"/> | Testing Laboratory: | Shenzhen CTB Testing Technology Co., Ltd. | |
| Testing location/ address: | | 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China | |
| Compiled by (name, signature): | | Jerry Qin |  |
| Reviewed by (name, signature): | | Finerb Bai |  |
| Approved by (name, signature): | | Kubo Lee |  |



List of Attachments (including a total number of pages in each attachment):

- ATTACHMENT 1: EN IEC 62368-1:2020+A11:2020 (NATIONAL DEVIATION) (21 pages)
- ATTACHMENT 2: PHOTO DOCUMENTATION (9 pages).

Summary of testing:

| | |
|--|--|
| Tests performed (name of test, test clause and date test performed): The submitted samples were found to comply with the requirements of: EN IEC 62368-1:2020+A11:2020 | Testing location: Shenzhen CTB Testing Technology Co., Ltd. 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China |
|--|--|

Summary of compliance with National Differences (List of countries addressed):

EU group differences.
CENELEC member countries (EU group differences): Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland.

The product fulfils the requirements of EN IEC 62368-1:2020+A11:2020.

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized.

| | | |
|--|---|--|
| Tablet PC(Notebook) | | |
| Model: MB02 | | |
| Ratings: 5V---2.0A | | |
| Battery Capacity: 3.85Vdc, 8000mAh, 30.8Wh | | |
|  |  |  |
| Importer: xxx | | Address: yyy |
| Creature Information(Guangzhou)Technology Co., Limited Room 404-05, No.4, Nengyuan Rd., Tianhe District, Guangzhou, China Made In China | | |

Remark for above marking:

1. The height of graphical symbols shall not be less than 5 mm;
2. The height of letters and numerals shall not be less than 2 mm;
3. The height dimension of CE mark should not less than 5mm, the height dimension of WEEE symbol should not less than 7mm.
4. The main rating label was attached in enclosure.
5. Markings of all models are identical except for model names and brand name.

Note: xxx means importer company name; yyy means importer company address information.
 Alternatively, Importer and importer address information provided in the instructions.

Possible test case verdicts:

- test case does not apply to the test object.....: N/A
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Date of receipt of test item.....: Feb. 07, 2025

Date (s) of performance of tests.....: Feb. 07, 2025 to Feb. 14, 2025

General remarks:

"(See Enclosure #)" refers to additional information appended to the report.

"(See appended table)" refers to a table appended to the report.

Throughout this report a comma / point is used as the decimal separator.

Name and address of factory (ies):

Creature Information(Guangzhou)Technology Co.,
Limited
Room 404-05, No.4, Nengyuan Rd., Tianhe District,
Guangzhou, China

General product information and other remarks:

- The appliance is Tablet PC(Notebook) and intended for indoor or similar condition used only.
- Max. operated temperature is considered as 25 °C for declared from manufacture.
- Instructions and equipment marking related to safety is applied in the language that is acceptable in the country in which the equipment is to be sold.
- In addition to section 10.6 and 10.4(Flash LED portion), the product meets the requirements of IEC 62368-1 standard.
- All models are identical to each other except for model name, unless otherwise specifies, all tests were performed on model MB02.

Series models as below:

| | |
|----------|--|
| Model(s) | <p>MB01, MB03, MB05, I7, I7 Plus, I7 Pro, I7 Power, I7 Turbo, I7 Ultra, I7 A, I7 A Plus, I7 A Pro, I7 A Power, I7 A Turbo, I7 A Ultra, I7 AI, I7 AI Plus, I7 AI Pro, I7 AI Power, I7 AI Turbo, I7 AI Ultra, I7 S, I7 S Plus, I7 S Pro, I7 S Power, I7 S Turbo, I7 S Ultra, I8, I8 Plus, I8 Pro, I8 Power, I8 Turbo, I8 Ultra, I8 A, I8 A Plus, I8 A Pro, I8 A Power, I8 A Turbo, I8 A Ultra, I8 AI, I8 AI Plus, I8 AI Pro, I8 AI Power, I8 AI Turbo, I8 AI Ultra, I8 S, I8 S Plus, I8 S Pro, I8 S Power, I8 S Turbo, I8 S Ultra, I9, I9 Plus, I9 Pro, I9 Power, I9 Turbo, I9 Ultra, I9 A, I9 A Plus, I9 A Pro, I9 A Power, I9 A Turbo, I9 A Ultra, I9 AI, I9 AI Plus, I9 AI Pro, I9 AI Power, I9 AI Turbo, I9 AI Ultra, I9 S, I9 S Plus, I9 S Pro, I9 S Power, I9 S Turbo, I9 S Ultra, I10, I10 Plus, I10 Pro, I10 Power, I10 Turbo, I10 Ultra, I10 A, I10 A Plus, I10 A Pro, I10 A Power, I10 A Turbo, I10 A Ultra, I10 AI, I10 AI Plus, I10 AI Pro, I10 AI Power, I10 AI Turbo, I10 AI Ultra, I10 S, I10 S Plus, I10 S Pro, I10 S Power, I10 S Turbo, I10 S Ultra, I11, I11 Plus, I11 Pro, I11 Power, I11 Turbo, I11 Ultra, I11 A, I11 A Plus, I11 A Pro, I11 A Power, I11 A Turbo, I11 A Ultra, I11 AI, I11 AI Plus, I11 AI Pro, I11 AI Power, I11 AI Turbo, I11 AI Ultra, I11 S, I11 S Plus, I11 S Pro, I11 S Power, I11 S Turbo, I11 S Ultra, I12, I12 Plus, I12 Pro, I12 Power, I12 Turbo, I12 Ultra, I12 A, I12 A Plus, I12 A Pro, I12 A Power, I12 A Turbo, I12 A Ultra, I12 AI, I12 AI Plus, I12 AI Pro, I12 AI Power, I12 AI Turbo, I12 AI Ultra, I12 S, I12 S Plus, I12 S Pro, I12 S Power, I12 S Turbo, I12 S Ultra, I13, I13 Plus, I13 Pro, I13 Power, I13 Turbo, I13 Ultra, I13 A, I13 A Plus, I13 A Pro, I13 A Power, I13 A Turbo, I13 A Ultra, I13 AI, I13 AI Plus, I13 AI Pro, I13 AI Power, I13 AI Turbo, I13 AI Ultra, I13 S, I13 S Plus, I13 S Pro, I13 S Power, I13 S Turbo, I13 S Ultra, T8, T8 Plus, T8 Pro, T8 Power, T8 Turbo, T8 Ultra, T8 A, T8 A Plus, T8 A Pro, T8 A Power, T8 A Turbo, T8 A Ultra, T8 AI, T8 AI Plus, T8 AI Pro, T8 AI Power, T8 AI Turbo, T8 AI Ultra, T8 S, T8 S Plus, T8 S Pro, T8 S Power, T8 S Turbo, T8 S Ultra, T10, T10 Plus, T10 Pro, T10 Power, T10 Turbo, T10 Ultra, T10 A, T10 A Plus, T10 A Pro, T10 A Power, T10 A Turbo, T10 A Ultra, T10 AI, T10 AI Plus, T10 AI Pro, T10 AI Power, T10 AI Turbo, T10 AI Ultra, T10 S, T10 S Plus, T10 S Pro, T10 S Power, T10 S Turbo, T10 S Ultra, T11, T11 Plus, T11 Pro, T11 Power, T11 Turbo, T11 Ultra, T11 A, T11 A Plus, T11 A Pro, T11 A Power, T11 A Turbo, T11 A Ultra, T11 AI, T11 AI Plus, T11 AI Pro, T11 AI Power, T11 AI Turbo, T11 AI Ultra, T11 S, T11 S Plus, T11 S Pro, T11 S Power, T11 S Turbo, T11 S Ultra, T12, T12 Plus, T12 Pro, T12 Power, T12 Turbo, T12 Ultra, T12 A, T12 A Plus, T12 A Pro, T12 A Power, T12 A Turbo, T12 A Ultra, T12 AI, T12 AI Plus, T12 AI Pro, T12 AI Power, T12 AI Turbo, T12 AI Ultra, T12 S, T12 S Plus, T12 S Pro, T12 S Power, T12 S Turbo, T12 S Ultra, T13, T13 Plus, T13 Pro, T13 Power, T13 Turbo, T13 Ultra, T13 A, T13 A Plus, T13 A Pro, T13 A Power, T13 A Turbo, T13 A Ultra, T13 AI, T13 AI Plus, T13 AI Pro, T13 AI Power, T13 AI Turbo, T13 AI Ultra, T13 S, T13 S Plus, T13 S Pro, T13 S Power, T13 S Turbo, T13 S Ultra, I6, I14, I15, I16</p> |
|----------|--|

Test item particulars:

Product group: end product built-in component

Classification of use by.....: Ordinary person Children likely present
 Instructed person
 Skilled person

Supply connection.....: AC mains DC mains
 not mains connected: (supplied by external power supply or rechargeable lithium battery)
 ES1 ES2 ES3

Supply tolerance: +10%/-10%
 +20%/-15%
 + %/ - %
 None

Supply connection – type: pluggable equipment type A -
 non-detachable supply cord
 appliance coupler
 direct plug-in
 pluggable equipment type B -
 non-detachable supply cord
 appliance coupler
 permanent connection
 mating connector other: supplied by external power supply or rechargeable lithium battery

Considered current rating of protective device.....: Location: building equipment
 N/A

Equipment mobility.....: movable hand-held transportable
 direct plug-in stationary for building-in
 wall/ceiling-mounted SRME/rack-mounted
 other:

Overvoltage category (OVC): OVC I OVC II OVC III
 OVC IV other: not directly connect to AC mains

Class of equipment: Class I Class II Class III
 Not classified

Special installation location: N/A restricted access area
 outdoor location

Pollution degree (PD): PD 1 PD 2 PD 3

Manufacturer’s specified T_{ma}.....: 25 °C Outdoor: minimum °C

IP protection class: IPX0 IP_____

Power systems: TN TT IT - V_{L-L}
 not AC mains

Altitude during operation (m): 2000 m or less m

Altitude of test laboratory (m): 2000 m or less m

Mass of equipment (kg): Approx. 0.525 kg

| OVERVIEW OF ENERGY SOURCES AND SAFEGUARDS | | | | |
|---|---|-------------|---|-------------------|
| Clause | Possible Hazard | | | |
| 5 | Electrically-caused injury | | | |
| Class and Energy Source (e.g. ES3: Primary circuit) | Body Part (e.g. Ordinary) | Safeguards | | |
| | | B | S | R |
| ES1: All the circuit | Ordinary person | N/A | N/A | N/A |
| 6 | Electrically-caused fire | | | |
| Class and Energy Source (e.g. PS2: 100 Watt circuit) | Material part (e.g. Printed board) | Safeguards | | |
| | | B | 1 st S | 2 nd S |
| PS2 | Enclosure | See 6.3.1 | See 6.4.3, 6.4.7 | N/A |
| PS2 | PCB | See 6.3.1 | V-1 or better | N/A |
| PS2 | Internal / external wiring | See 6.3.1 | See 6.5 (Equipment safeguards, rated VW-1) | N/A |
| PS2 | Other combustible components / materials | See 6.3.1 | See 6.4.5, 6.4.6 | N/A |
| PS2 | Li-ion battery | See 6.3 | See 6.4.5 | N/A |
| 7 | Injury caused by hazardous substances | | | |
| Class and Energy Source (e.g. Ozone) | Body Part (e.g., Skilled) | Safeguards | | |
| | | B | S | R |
| Lithium-ion Polymer | Battery and their protection circuit | See Annex M | N/A | N/A |
| 8 | Mechanically-caused injury | | | |
| Class and Energy Source (e.g. MS3: Plastic fan blades) | Body Part (e.g. Ordinary) | Safeguards | | |
| | | B | S | R |
| MS1: Sharp edges and corners | Ordinary person | N/A | N/A | N/A |
| MS1: Equipment mass | Ordinary person | N/A | N/A | N/A |
| 9 | Thermal burn | | | |
| Class and Energy Source (e.g. TS1: Keyboard caps) | Body Part (e.g., Ordinary) | Safeguards | | |
| | | B | S | R |
| TS1: External accessible parts | Ordinary person | N/A | N/A | N/A |
| 10 | Radiation | | | |
| Class and Energy Source (e.g. RS1: PMP sound output) | Body Part (e.g., Ordinary) | Safeguards | | |
| | | B | S | R |
| RS1: LED panel | Ordinary person | N/A | N/A | N/A |
| RS1: LED indicator light | Ordinary person | N/A | N/A | N/A |
| Supplementary Information: | | | | |

“B” – Basic Safeguard; “S” – Supplementary Safeguard; “R” – Reinforced Safeguard

ENERGY SOURCE DIAGRAM

Optional. Manufacturers are to provide the energy sources diagram identify declared energy sources and identifying the demarcations are between power sources. Recommend diagram be provided included in power supply and multipart systems.

Insert diagram below. Example diagram designs are; Block diagrams; image(s) with layered data; mechanical drawings

ES PS MS TS RS

(See OVERVIEW OF ENERGY SOURCES AND SAFEGUARDS)

| IEC 62368-1 | | | |
|-------------|--|--|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 4 | GENERAL REQUIREMENTS | | P |
| 4.1.1 | Acceptance of materials, components and subassemblies | (See appended Table 4.1.2.) | P |
| 4.1.2 | Use of components | Safeguard components are certified to IEC and/or national standards and are used correctly within their ratings. | P |
| 4.1.3 | Equipment design and construction | | P |
| 4.1.4 | Specified ambient temperature for outdoor use (°C) : | | N/A |
| 4.1.5 | Constructions and components not specifically covered | | P |
| 4.1.8 | Liquids and liquid filled components (LFC) | (See G.15) | N/A |
| 4.1.15 | Markings and instructions | (See Annex F) | P |
| 4.4.3 | Safeguard robustness | See below | P |
| 4.4.3.1 | General | | P |
| 4.4.3.2 | Steady force tests | (See Annex T.4) | P |
| 4.4.3.3 | Drop tests | (See Annex T.7) | P |
| 4.4.3.4 | Impact tests | | N/A |
| 4.4.3.5 | Internal accessible safeguard tests | | N/A |
| 4.4.3.6 | Glass impact tests | | N/A |
| 4.4.3.7 | Glass fixation tests | | N/A |
| | Glass impact test (1J) | | N/A |
| | Push/pull test (10 N) | | N/A |
| 4.4.3.8 | Thermoplastic material tests | (See Annex T.8) | P |
| 4.4.3.9 | Air comprising a safeguard | Complied | N/A |
| 4.4.3.10 | Accessibility, glass, safeguard effectiveness | All safeguards remain effective. | P |
| 4.4.4 | Displacement of a safeguard by an insulating liquid | | N/A |
| 4.4.5 | Safety interlocks | (See Annex K) | N/A |
| 4.5 | Explosion | | P |
| 4.5.1 | General | No explosion observed during normal / abnormal / single fault conditions. | P |
| 4.5.2 | No explosion during normal/abnormal operating condition | (See Clause B.2, B.3) | P |
| | No harm by explosion during single fault conditions | (See Clause B.4) | P |
| 4.6 | Fixing of conductors | | N/A |
| | Fix conductors not to defeat a safeguard | | N/A |

| IEC 62368-1 | | | |
|-------------|---|--------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Compliance is checked by test..... : | | N/A |
| 4.7 | Equipment for direct insertion into mains socket-outlets | | N/A |
| 4.7.2 | Mains plug part complies with relevant standard... : | | N/A |
| 4.7.3 | Torque (Nm)..... : | | N/A |
| 4.8 | Equipment containing coin/button cell batteries | | N/A |
| 4.8.1 | General | | N/A |
| 4.8.2 | Instructional safeguard..... : | Not such construction | N/A |
| 4.8.3 | Battery compartment door/cover construction | | N/A |
| | Open torque test | | N/A |
| 4.8.4.2 | Stress relief test | | N/A |
| 4.8.4.3 | Battery replacement test | | N/A |
| 4.8.4.4 | Drop test | (See Clause T.7) | N/A |
| 4.8.4.5 | Impact test | | N/A |
| 4.8.4.6 | Crush test | | N/A |
| 4.8.5 | Compliance | | N/A |
| | 30N force test with test probe | | N/A |
| | 20N force test with test hook | | N/A |
| 4.9 | Likelihood of fire or shock due to entry of conductive object | | N/A |
| 4.10 | Component requirements | | N/A |
| 4.10.1 | Disconnect Device | (See Annex L) | N/A |
| 4.10.2 | Switches and relays | (See Annex G) | N/A |
| 5 | ELECTRICALLY-CAUSED INJURY | | P |
| 5.2 | Classification and limits of electrical energy sources | | P |
| 5.2.2 | ES1, ES2 and ES3 limits | ES1 | P |
| 5.2.2.2 | Steady-state voltage and current limits..... : | (See appended table 5.2) | P |
| 5.2.2.3 | Capacitance limits..... : | | N/A |
| 5.2.2.4 | Single pulse limits..... : | | N/A |
| 5.2.2.5 | Limits for repetitive pulses..... : | | N/A |
| 5.2.2.6 | Ringing signals | | N/A |
| 5.2.2.7 | Audio signals | (See Clause E.1) | P |
| 5.3 | Protection against electrical energy sources | | N/A |
| 5.3.1 | General Requirements for accessible parts to ordinary, instructed and skilled persons | See below. | N/A |
| 5.3.1 a) | Accessible ES1/ES2 derived from ES2/ES3 circuits | | N/A |

| IEC 62368-1 | | | |
|-------------|---|--|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5.3.1 b) | Skilled persons not unintentional contact ES3 bare conductors | | N/A |
| 5.3.2.1 | Accessibility to electrical energy sources and safeguards | Only ES1 circuit can be accessed for this product. | N/A |
| | Accessibility to outdoor equipment bare parts | | N/A |
| 5.3.2.2 | Contact requirements | | N/A |
| | Test with test probe from Annex V | | — |
| 5.3.2.2 a) | Air gap – electric strength test potential (V)..... : | | N/A |
| 5.3.2.2 b) | Air gap – distance (mm) : | | N/A |
| 5.3.2.3 | Compliance | | N/A |
| 5.3.2.4 | Terminals for connecting stripped wire | | N/A |
| 5.4 | Insulation materials and requirements | | N/A |
| 5.4.1.2 | Properties of insulating material | | N/A |
| 5.4.1.3 | Material is non-hygroscopic | | N/A |
| 5.4.1.4 | Maximum operating temperature for insulating materials..... : | | N/A |
| 5.4.1.5 | Pollution degrees..... : | | N/A |
| 5.4.1.5.2 | Test for pollution degree 1 environment and for an insulating compound | | N/A |
| 5.4.1.5.3 | Thermal cycling test | | N/A |
| 5.4.1.6 | Insulation in transformers with varying dimensions | | N/A |
| 5.4.1.7 | Insulation in circuits generating starting pulses | | N/A |
| 5.4.1.8 | Determination of working voltage..... : | | N/A |
| 5.4.1.9 | Insulating surfaces | | N/A |
| 5.4.1.10 | Thermoplastic parts on which conductive metallic parts are directly mounted | | N/A |
| 5.4.1.10.2 | Vicat test..... : | | N/A |
| 5.4.1.10.3 | Ball pressure test..... : | | N/A |
| 5.4.2 | Clearances | | N/A |
| 5.4.2.1 | General requirements | | N/A |
| | Clearances in circuits connected to AC Mains, Alternative method | | N/A |
| 5.4.2.2 | Procedure 1 for determining clearance | | N/A |
| | Temporary overvoltage : | | — |
| 5.4.2.3 | Procedure 2 for determining clearance | | N/A |
| 5.4.2.3.2.2 | a.c. mains transient voltage..... : | | — |
| 5.4.2.3.2.3 | d.c. mains transient voltage : | -- | — |

| IEC 62368-1 | | | |
|-------------|--|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5.4.2.3.2.4 | External circuit transient voltage..... : | -- | --- |
| 5.4.2.3.2.5 | Transient voltage determined by measurement..... : | -- | --- |
| 5.4.2.4 | Determining the adequacy of a clearance using an electric strength test | (See appended table 5.4.2) | N/A |
| 5.4.2.5 | Multiplication factors for clearances and test voltages | | N/A |
| 5.4.2.6 | Clearance measurement..... : | | N/A |
| 5.4.3 | Creepage distances | | N/A |
| 5.4.3.1 | General | | N/A |
| 5.4.3.3 | Material group..... : | | --- |
| 5.4.3.4 | Creepage distances measurement..... : | (See appended table 5.4.3) | N/A |
| 5.4.4 | Solid insulation | | N/A |
| 5.4.4.1 | General requirements | | N/A |
| 5.4.4.2 | Minimum distance through insulation | (See appended table 5.4.4.2) | N/A |
| 5.4.4.3 | Insulating compound forming solid insulation | | N/A |
| 5.4.4.4 | Solid insulation in semiconductor devices | | N/A |
| 5.4.4.5 | Insulating compound forming cemented joints | | N/A |
| 5.4.4.6 | Thin sheet material | | N/A |
| 5.4.4.6.1 | General requirements | | N/A |
| 5.4.4.6.2 | Separable thin sheet material | | N/A |
| | Number of layers (pcs) | | N/A |
| 5.4.4.6.3 | Non-separable thin sheet material | | N/A |
| | Number of layers (pcs) | | N/A |
| 5.4.4.6.4 | Standard test procedure for non-separable thin sheet material..... : | (See appended table 5.4.9) | N/A |
| 5.4.4.6.5 | Mandrel test | | N/A |
| 5.4.4.7 | Solid insulation in wound components | (See Annex G5 and G6) | N/A |
| 5.4.4.9 | Solid insulation at frequencies >30 kHz, E_P , K_R , d , V_{PW} (V)..... : | (See appended Table 5.4.4.9) | N/A |
| | Alternative by electric strength test, tested voltage (V), K_R : | (See appended Tables 5.4.4.9 and 5.4.9) | N/A |
| 5.4.5 | Antenna terminal insulation | | N/A |
| 5.4.5.1 | General | | N/A |
| 5.4.5.2 | Voltage surge test | | N/A |
| 5.4.5.3 | Insulation resistance (M Ω)..... : | | N/A |
| | Electric strength test..... : | (See appended table 5.4.9) | N/A |

| IEC 62368-1 | | | |
|-------------|--|----------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5.4.6 | Insulation of internal wire as part of supplementary safeguard | | N/A |
| 5.4.7 | Tests for semiconductor components and for cemented joints | | N/A |
| 5.4.8 | Humidity conditioning | | N/A |
| | Relative humidity (%), temperature (°C), duration (h)..... : | | — |
| 5.4.9 | Electric strength test | (See appended table 5.4.9) | N/A |
| 5.4.9.1 | Test procedure for type test of solid insulation..... : | Method 1 used. | N/A |
| 5.4.9.2 | Test procedure for routine test | | N/A |
| 5.4.10 | Safeguards against transient voltages from external circuits | | N/A |
| 5.4.10.1 | Parts and circuits separated from external circuits | | N/A |
| 5.4.10.2 | Test methods | | N/A |
| 5.4.10.2.1 | General | | N/A |
| 5.4.10.2.2 | Impulse test..... : | (See appended table 5.4.9) | N/A |
| 5.4.10.2.3 | Steady-state test..... : | (See appended table 5.4.9) | N/A |
| 5.4.10.3 | Verification for insulation breakdown for impulse test..... : | | N/A |
| 5.4.11 | Separation between external circuits and earth | | N/A |
| 5.4.11.1 | Exceptions to separation between external circuits and earth | | N/A |
| 5.4.11.2 | Requirements | | N/A |
| | SPDs bridge separation between external circuit and earth | | N/A |
| | Rated operating voltage U_{op} (V)..... : | | — |
| | Nominal voltage U_{peak} (V)..... : | | — |
| | Max increase due to variation ΔU_{sp} | | — |
| | Max increase due to ageing ΔU_{sa} | | — |
| 5.4.11.3 | Test method and compliance..... : | (See appended table 5.4.9) | N/A |
| 5.4.12 | Insulating liquid | | N/A |
| 5.4.12.1 | General requirements | | N/A |
| 5.4.12.2 | Electric strength of an insulating liquid..... : | (See appended table 5.4.9) | N/A |
| 5.4.12.3 | Compatibility of an insulating liquid..... : | (See appended table 5.4.9) | N/A |
| 5.4.12.4 | Container for insulating liquid..... : | | N/A |
| 5.5 | Components as safeguards | | N/A |
| 5.5.1 | General | | N/A |

| IEC 62368-1 | | | |
|-------------|---|----------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5.5.2 | Capacitors and RC units | | N/A |
| 5.5.2.1 | General requirement | | N/A |
| 5.5.2.2 | Safeguards against capacitor discharge after disconnection of a connector..... : | | N/A |
| 5.5.3 | Transformers | (See Annex G.5.3) | N/A |
| 5.5.4 | Optocouplers | (See appended table 4.1.2) | N/A |
| 5.5.5 | Relays | (See sub-clause 5.4) | N/A |
| 5.5.6 | Resistors | (See Clause G.10) | N/A |
| 5.5.7 | SPDs | (See Clause G.8) | N/A |
| 5.5.8 | Insulation between the mains and an external circuit consisting of a coaxial cable..... : | | N/A |
| 5.5.9 | Safeguards for socket-outlets in outdoor equipment | | N/A |
| | RCD rated residual operating current (mA)..... : | | — |
| 5.6 | Protective conductor | | N/A |
| 5.6.2 | Requirement for protective conductors | | N/A |
| 5.6.2.1 | General requirements | | N/A |
| 5.6.2.2 | Colour of insulation | | N/A |
| 5.6.3 | Requirement for protective earthing conductors | | N/A |
| | Protective earthing conductor size (mm ²) : | | — |
| | Protective earthing conductor serving as a reinforced safeguard | | N/A |
| | Protective earthing conductor serving as a double safeguard | | N/A |
| 5.6.4 | Requirements for protective bonding conductors | | N/A |
| 5.6.4.1 | Protective bonding conductors | | N/A |
| | Protective bonding conductor size (mm ²)..... : | (see table 4.1.2) | — |
| 5.6.4.2 | Protective current rating (A)..... : | | N/A |
| 5.6.5 | Terminals for protective conductors | | N/A |
| 5.6.5.1 | Terminal size for connecting protective earthing conductors (mm)..... : | | N/A |
| | Terminal size for connecting protective bonding conductors (mm)..... : | | N/A |
| 5.6.5.2 | Corrosion | | N/A |
| 5.6.6 | Resistance of the protective bonding system | | N/A |
| 5.6.6.1 | Requirements | | N/A |
| 5.6.6.2 | Test Method..... : | (See appended table 5.6.6) | N/A |
| 5.6.6.3 | Resistance (Ω) or voltage drop..... : | (See appended table 5.6.6) | N/A |

| IEC 62368-1 | | | |
|-------------|---|----------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 5.6.7 | Reliable connection of a protective earthing conductor | | N/A |
| 5.6.8 | Functional earthing | | N/A |
| | Conductor size (mm ²)..... : | | N/A |
| | Class II with functional earthing marking : | | N/A |
| | Appliance inlet cl & cr (mm)..... : | | N/A |
| 5.7 | Prospective touch voltage, touch current and protective conductor current | | N/A |
| 5.7.2 | Measuring devices and networks | | N/A |
| 5.7.2.1 | Measurement of touch current | (See appended table 5.7.4) | N/A |
| 5.7.2.2 | Measurement of voltage | (See appended table 5.7.4) | N/A |
| 5.7.3 | Equipment set-up, supply connections and earth connections | | N/A |
| 5.7.4 | Unearthed accessible parts..... : | (See appended table 5.7.4) | N/A |
| 5.7.5 | Earthed accessible conductive parts..... : | (See appended table 5.7.5) | N/A |
| 5.7.6 | Requirements when touch current exceeds ES2 limits | | N/A |
| | Protective conductor current (mA)..... : | | N/A |
| | Instructional Safeguard..... : | | N/A |
| 5.7.7 | Prospective touch voltage and touch current associated with external circuits | | N/A |
| 5.7.7.1 | Touch current from coaxial cables | | N/A |
| 5.7.7.2 | Prospective touch voltage and touch current associated with paired conductor cables | | N/A |
| 5.7.8 | Summation of touch currents from external circuits | | N/A |
| | a) Equipment connected to earthed external circuits, current (mA)..... : | | N/A |
| | b) Equipment connected to unearthed external circuits, current (mA)..... : | | N/A |
| 5.8 | Backfeed safeguard in battery backed up supplies | | N/A |
| | Mains terminal ES..... : | (See appended table 5.8) | N/A |
| | Air gap (mm)..... : | | N/A |

| | | | |
|------------|--|---|-----|
| 6 | ELECTRICALLY- CAUSED FIRE | | P |
| 6.2 | Classification of PS and PIS | | P |
| 6.2.2 | Power source circuit classifications..... : | See overview of energy sources and safeguards | P |
| 6.2.3 | Classification of potential ignition sources | See overview of energy sources and safeguards | P |
| 6.2.3.1 | Arcing PIS : | | N/A |

| IEC 62368-1 | | | |
|-------------|---|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 6.2.3.2 | Resistive PIS | All circuits within equipment | P |
| 6.3 | Safeguards against fire under normal operating and abnormal operating conditions | | P |
| 6.3.1 | No ignition and attainable temperature value less than 90 % defined by ISO 871 or less than 300 °C for unknown materials..... | (See appended table 5.4.1.4, 9.3, B.1.5, B.2.6) | P |
| | Combustible materials outside fire enclosure..... | HB or HBF min. | P |
| 6.4 | Safeguards against fire under single fault conditions | | P |
| 6.4.1 | Safeguard method | Method of Control fire spread used. | P |
| 6.4.2 | Reduction of the likelihood of ignition under single fault conditions in PS1 circuits | | P |
| 6.4.3 | Reduction of the likelihood of ignition under single fault conditions in PS2 and PS3 circuits | | P |
| 6.4.3.1 | Supplementary safeguards | | P |
| 6.4.3.2 | Single Fault Conditions..... | (See appended table B.3, B.4) | P |
| | Special conditions for temperature limited by fuse | | N/A |
| 6.4.4 | Control of fire spread in PS1 circuits | | P |
| 6.4.5 | Control of fire spread in PS2 circuits | See below. | P |
| 6.4.5.2 | Supplementary safeguards | Compliance detailed as follows: – Printed board: rated min. V-1 class material; – The battery packs: complying with IEC 62133-2. – All other components: at least V-2 except for parts mounted on min. V-1 material or small parts of combustible material (with mass less than 4g). The internal wires were complied to UL 758 standard, which test method and testing condition equal to IEC/EN 60695-11-21 | P |
| 6.4.6 | Control of fire spread in PS3 circuits | | N/A |
| 6.4.7 | Separation of combustible materials from a PIS | | N/A |
| 6.4.7.2 | Separation by distance | | N/A |
| 6.4.7.3 | Separation by a fire barrier | | N/A |
| 6.4.8 | Fire enclosures and fire barriers | Metal enclosure provided as fire enclosure. | P |
| 6.4.8.2 | Fire enclosure and fire barrier material properties | | P |

| IEC 62368-1 | | | |
|-------------|--|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 6.4.8.2.1 | Requirements for a fire barrier | | N/A |
| 6.4.8.2.2 | Requirements for a fire enclosure | | P |
| 6.4.8.3 | Constructional requirements for a fire enclosure and a fire barrier | See below | P |
| 6.4.8.3.1 | Fire enclosure and fire barrier openings | | N/A |
| 6.4.8.3.2 | Fire barrier dimensions | | N/A |
| 6.4.8.3.3 | Top openings and properties | No openings | N/A |
| | Openings dimensions (mm)..... : | | N/A |
| 6.4.8.3.4 | Bottom openings and properties | No openings | N/A |
| | Openings dimensions (mm)..... : | | N/A |
| | Flammability tests for the bottom of a fire enclosure | | N/A |
| | Instructional Safeguard..... : | | N/A |
| 6.4.8.3.5 | Side openings and properties | | N/A |
| | Openings dimensions (mm)..... : | | N/A |
| 6.4.8.3.6 | Integrity of a fire enclosure, condition met: a), b) or c)..... : | | N/A |
| 6.4.8.4 | Separation of a PIS from a fire enclosure and a fire barrier distance (mm) or flammability rating..... : | | N/A |
| 6.4.9 | Flammability of insulating liquid..... : | | N/A |
| 6.5 | Internal and external wiring | | P |
| 6.5.1 | General requirements | The material of VW-1 on internal wiring were considered compliance equal to equivalent to IEC/TS 60695-11-21 relevant standards | P |
| 6.5.2 | Requirements for interconnection to building wiring : | No such interconnection to building wiring. | N/A |
| 6.5.3 | Internal wiring size (mm ²) for socket-outlets..... : | No socket-outlet used. | N/A |
| 6.6 | Safeguards against fire due to the connection to additional equipment | | P |
| 7 | INJURY CAUSED BY HAZARDOUS SUBSTANCES | | P |
| 7.2 | Reduction of exposure to hazardous substances | | N/A |
| 7.3 | Ozone exposure | | N/A |
| 7.4 | Use of personal safeguards or personal protective equipment (PPE) | | N/A |
| | Personal safeguards and instructions..... : | | — |
| 7.5 | Use of instructional safeguards and instructions | | N/A |
| | Instructional safeguard (ISO 7010)..... : | | — |
| 7.6 | Batteries and their protection circuits | | P |

| IEC 62368-1 | | | |
|-------------|---|--|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 8 | MECHANICALLY-CAUSED INJURY | | P |
| 8.2 | Mechanical energy source classifications | | P |
| 8.3 | Safeguards against mechanical energy sources | | P |
| 8.4 | Safeguards against parts with sharp edges and corners | | P |
| 8.4.1 | Safeguards | | N/A |
| | Instructional Safeguard..... : | | N/A |
| 8.4.2 | Sharp edges or corners | Accessible edges and corners of the equipment are rounded and are classified as MS1. | P |
| 8.5 | Safeguards against moving parts | | N/A |
| 8.5.1 | Fingers, jewellery, clothing, hair, etc., contact with MS2 or MS3 parts | | N/A |
| | MS2 or MS3 part required to be accessible for the function of the equipment | | N/A |
| | Moving MS3 parts only accessible to skilled person | | N/A |
| 8.5.2 | Instructional safeguard..... : | | N/A |
| 8.5.4 | Special categories of equipment containing moving parts | | N/A |
| 8.5.4.1 | General | | N/A |
| 8.5.4.2 | Equipment containing work cells with MS3 parts | | N/A |
| 8.5.4.2.1 | Protection of persons in the work cell | | N/A |
| 8.5.4.2.2 | Access protection override | | N/A |
| 8.5.4.2.2.1 | Override system | | N/A |
| 8.5.4.2.2.2 | Visual indicator | | N/A |
| 8.5.4.2.3 | Emergency stop system | | N/A |
| | Maximum stopping distance from the point of activation (m)..... : | | N/A |
| | Space between end point and nearest fixed mechanical part (mm)..... : | | N/A |
| 8.5.4.2.4 | Endurance requirements | | N/A |
| | Mechanical system subjected to 100 000 cycles of operation | | N/A |
| | - Mechanical function check and visual inspection | | N/A |
| | - Cable assembly..... : | | N/A |
| 8.5.4.3 | Equipment having electromechanical device for destruction of media | | N/A |
| 8.5.4.3.1 | Equipment safeguards | | N/A |
| 8.5.4.3.2 | Instructional safeguards against moving parts..... : | | N/A |

| IEC 62368-1 | | | |
|-------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 8.5.4.3.3 | Disconnection from the supply | | N/A |
| 8.5.4.3.4 | Cut type and test force (N)..... : | | N/A |
| 8.5.4.3.5 | Compliance | | N/A |
| 8.5.5 | High pressure lamps | | N/A |
| | Explosion test..... : | | N/A |
| 8.5.5.3 | Glass particles dimensions (mm)..... : | | N/A |
| 8.6 | Stability of equipment | | N/A |
| 8.6.1 | General | MS1 | N/A |
| | Instructional safeguard..... : | | N/A |
| 8.6.2 | Static stability | | N/A |
| 8.6.2.2 | Static stability test..... : | | N/A |
| 8.6.2.3 | Downward force test | | N/A |
| 8.6.3 | Relocation stability | | N/A |
| | Wheels diameter (mm)..... : | | — |
| | Tilt test | | N/A |
| 8.6.4 | Glass slide test | | N/A |
| 8.6.5 | Horizontal force test..... : | | N/A |
| 8.7 | Equipment mounted to wall, ceiling or other structure | | N/A |
| 8.7.1 | Mount means type..... : | | N/A |
| 8.7.2 | Test methods | | N/A |
| | Test 1, additional downwards force (N)..... : | | N/A |
| | Test 2, number of attachment points and test force (N)..... : | | N/A |
| | Test 3 Nominal diameter (mm) and applied torque (Nm)..... : | | N/A |
| 8.8 | Handles strength | | N/A |
| 8.8.1 | General | No handle | N/A |
| 8.8.2 | Handle strength test | | N/A |
| | Number of handles..... : | | — |
| | Force applied (N)..... : | | N/A |
| 8.9 | Wheels or casters attachment requirements | | N/A |
| 8.9.2 | Pull test | | N/A |
| 8.10 | Carts, stands and similar carriers | | N/A |
| 8.10.1 | General | | N/A |
| 8.10.2 | Marking and instructions..... : | | N/A |

| IEC 62368-1 | | | |
|-------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 8.10.3 | Cart, stand or carrier loading test | | N/A |
| | Loading force applied (N)..... : | | N/A |
| 8.10.4 | Cart, stand or carrier impact test | | N/A |
| 8.10.5 | Mechanical stability | | N/A |
| | Force applied (N)..... : | | N/A |
| 8.10.6 | Thermoplastic temperature stability | | N/A |
| 8.11 | Mounting means for slide-rail mounted equipment (SRME) | | N/A |
| 8.11.1 | General | | N/A |
| 8.11.2 | Requirements for slide rails | | N/A |
| | Instructional Safeguard..... : | | N/A |
| 8.11.3 | Mechanical strength test | | N/A |
| 8.11.3.1 | Downward force test, force (N) applied..... : | | N/A |
| 8.11.3.2 | Lateral push force test | | N/A |
| 8.11.3.3 | Integrity of slide rail end stops | | N/A |
| 8.11.4 | Compliance | | N/A |
| 8.12 | Telescoping or rod antennas | | N/A |
| | Button/ball diameter (mm)..... : | | — |

| | | | |
|------------|---|--------------------------|-----|
| 9 | THERMAL BURN INJURY | | P |
| 9.2 | Thermal energy source classifications | | P |
| 9.3 | Touch temperature limits | | P |
| 9.3.1 | Touch temperatures of accessible parts..... : | (See appended table 9.3) | P |
| 9.3.2 | Test method and compliance | | P |
| 9.4 | Safeguards against thermal energy sources | | N/A |
| 9.5 | Requirements for safeguards | | N/A |
| 9.5.1 | Equipment safeguard | | N/A |
| 9.5.2 | Instructional safeguard..... : | | N/A |
| 9.6 | Requirements for wireless power transmitters | | N/A |
| 9.6.1 | General | | N/A |
| 9.6.2 | Specification of the foreign objects | | N/A |
| 9.6.3 | Test method and compliance..... : | (See appended table 9.6) | N/A |

| | | | |
|-------------|---|---|---|
| 10 | RADIATION | | P |
| 10.2 | Radiation energy source classification | | P |
| 10.2.1 | General classification | See Energy source identification and classification | P |

| IEC 62368-1 | | | |
|--------------|---|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | | table. | |
| | Lasers..... : | | — |
| | Lamps and lamp systems..... : | RS1 | — |
| | Image projectors..... : | | — |
| | X-Ray..... : | | — |
| | Personal music player..... : | | — |
| 10.3 | Safeguards against laser radiation | | N/A |
| | The standard(s) equipment containing laser(s) comply..... : | No laser radiation | N/A |
| 10.4* | Safeguards against optical radiation from lamps and lamp systems (including LED types) | | P |
| 10.4.1 | General requirements | LED panel: The luminance of LED panel is far less than 1000cd/m ² . With reference to subclause 4.1 of IEC 62471:2006 no further test is necessary, LED panel are considered as RS1. LED indicator light: LED indicator lights are considered as RS1. | P |
| | Instructional safeguard provided for accessible radiation level needs to exceed | | N/A |
| | Risk group marking and location..... : | | N/A |
| | Information for safe operation and installation | | N/A |
| 10.4.2 | Requirements for enclosures | | N/A |
| | UV radiation exposure..... : | (See Annex C) | N/A |
| 10.4.3 | Instructional safeguard..... : | | N/A |
| 10.5 | Safeguards against X-radiation | | N/A |
| 10.5.1 | Requirements | No X-radiation | N/A |
| | Instructional safeguard for skilled persons..... : | | — |
| 10.5.3 | Maximum radiation (pA/kg)..... : | (See appended tables B.3 & B.4) | — |
| 10.6* | Safeguards against acoustic energy sources | | — |
| 10.6.1 | General | | — |
| 10.6.2 | Classification | | — |
| | Acoustic output $L_{Aeq,T}$, dB(A)..... : | | — |
| | Unweighted RMS output voltage (mV)..... : | | — |
| | Digital output signal (dBFS)..... : | | — |

| IEC 62368-1 | | | |
|-------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| 10.6.3 | Requirements for dose-based systems | | — |
| 10.6.3.1 | General requirements | | — |
| 10.6.3.2 | Dose-based warning and automatic decrease | | — |
| 10.6.3.3 | Exposure-based warning and requirements | | — |
| | 30 s integrated exposure level (MEL30)..... : | | — |
| | Warning for MEL ≥ 100 dB(A)..... : | | — |
| 10.6.4 | Measurement methods | | — |
| 10.6.5 | Protection of persons | | — |
| | Instructional safeguards..... : | | — |
| 10.6.6 | Requirements for listening devices (headphones, earphones, etc.) | | — |
| 10.6.6.1 | Corded listening devices with analogue input | | — |
| | Listening device input voltage (mV)..... : | | — |
| 10.6.6.2 | Corded listening devices with digital input | | — |
| | Max. acoustic output $L_{Aeq,T}$, dB(A)..... : | | — |
| 10.6.6.3 | Cordless listening devices | | — |
| | Max. acoustic output $L_{Aeq,T}$, dB(A)..... : | | — |

| | | | |
|------------|--|--|-----|
| B | NORMAL OPERATING CONDITION TESTS, ABNORMAL OPERATING CONDITION TESTS AND SINGLE FAULT CONDITION TESTS | | P |
| B.1 | General | | P |
| B.1.5 | Temperature measurement conditions | (See appended table B.1.5) | P |
| B.2 | Normal operating conditions | | P |
| B.2.1 | General requirements..... : | (See Test Item Particulars and appended test tables) | P |
| | Audio Amplifiers and equipment with audio amplifiers..... : | (See Annex E) | P |
| B.2.3 | Supply voltage and tolerances | Not mains connected | N/A |
| B.2.5 | Input test..... : | (See appended table B.2.5) | P |
| B.3 | Simulated abnormal operating conditions | | P |
| B.3.1 | General | (See appended table B.3, B.4) | P |
| B.3.2 | Covering of ventilation openings | | N/A |
| | Instructional safeguard..... : | | N/A |
| B.3.3 | DC mains polarity test | | N/A |
| B.3.4 | Setting of voltage selector | No voltage selector | N/A |
| B.3.5 | Maximum load at output terminals | (See appended table B.3, B.4) | N/A |

| IEC 62368-1 | | | |
|-------------|---|-------------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| B.3.6 | Reverse battery polarity | | N/A |
| B.3.7 | Audio amplifier abnormal operating conditions | (See Annex E) | P |
| B.3.8 | Safeguards functional during and after abnormal operating conditions..... : | (See appended table B.3, B.4) | P |
| B.4 | Simulated single fault conditions | | P |
| B.4.1 | General | | P |
| B.4.2 | Temperature controlling device | | N/A |
| B.4.3 | Blocked motor test | | N/A |
| B.4.4 | Functional insulation | (See appended table B.3, B.4) | P |
| B.4.4.1 | Short circuit of clearances for functional insulation | | P |
| B.4.4.2 | Short circuit of creepage distances for functional insulation | | P |
| B.4.4.3 | Short circuit of functional insulation on coated printed boards | | N/A |
| B.4.5 | Short-circuit and interruption of electrodes in tubes and semiconductors | (See appended table B.3, B.4) | N/A |
| B.4.6 | Short circuit or disconnection of passive components | (See appended table B.3, B.4) | N/A |
| B.4.7 | Continuous operation of components | | N/A |
| B.4.8 | Compliance during and after single fault conditions..... : | (See appended table B.3, B.4) | P |
| B.4.9 | Battery charging and discharging under single fault conditions | (See Annex M) | P |
| C | UV RADIATION | | N/A |
| C.1 | Protection of materials in equipment from UV radiation | | N/A |
| C.1.2 | Requirements | | N/A |
| C.1.3 | Test method | | N/A |
| C.2 | UV light conditioning test | | N/A |
| C.2.1 | Test apparatus..... : | | N/A |
| C.2.2 | Mounting of test samples | | N/A |
| C.2.3 | Carbon-arc light-exposure test | | N/A |
| C.2.4 | Xenon-arc light-exposure test | | N/A |
| D | TEST GENERATORS | | N/A |
| D.1 | Impulse test generators | | N/A |
| D.2 | Antenna interface test generator | | N/A |
| D.3 | Electronic pulse generator | | N/A |
| E | TEST CONDITIONS FOR EQUIPMENT CONTAINING AUDIO AMPLIFIERS | | P |
| E.1 | Electrical energy source classification for audio signals | | P |

| IEC 62368-1 | | | |
|-------------|---|--|----------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Maximum non-clipped output power (W)..... : | | — |
| | Rated load impedance (Ω) | | — |
| | Open-circuit output voltage (V)..... : | | — |
| | Instructional safeguard..... : | No safeguard necessary | — |
| E.2 | Audio amplifier normal operating conditions | | P |
| | Audio signal source type..... : | 1KHz | — |
| | Audio output power (W)..... : | | — |
| | Audio output voltage (V)..... : | | — |
| | Rated load impedance (Ω) | | — |
| | Requirements for temperature measurement | (See appended table B.1.5) Test with maximum volume. | P |
| E.3 | Audio amplifier abnormal operating conditions | (See appended table B.3, B.4) Test with maximum volume. | P |
| F | EQUIPMENT MARKINGS, INSTRUCTIONS, AND INSTRUCTIONAL SAFEGUARDS | | P |
| F.1 | General | | P |
| | Language | English. Versions in other languages will be provided when national certificate approval. | — |
| F.2 | Letter symbols and graphical symbols | | P |
| F.2.1 | Letter symbols according to IEC60027-1 | | N/A |
| F.2.2 | Graphic symbols according to IEC, ISO or manufacturer specific | | P |
| F.3 | Equipment markings | | P |
| F.3.1 | Equipment marking locations | The equipment marking is located on the surface and is easily visible. | P |
| F.3.2 | Equipment identification markings | See below. | P |
| F.3.2.1 | Manufacturer identification | See copy of marking plate | P |
| F.3.2.2 | Model identification | See copy of marking plate | P |
| F.3.3 | Equipment rating markings | See below. | P |
| F.3.3.1 | Equipment with direct connection to mains | | N/A |
| F.3.3.2 | Equipment without direct connection to mains | See copy of marking plate | P |
| F.3.3.3 | Nature of the supply voltage..... : | See copy of marking plate | P |
| F.3.3.4 | Rated voltage..... : | See copy of marking plate | P |
| F.3.3.5 | Rated frequency..... : | | N/A |

| IEC 62368-1 | | | |
|-------------|---|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| F.3.3.6 | Rated current or rated power..... : | See copy of marking plate | P |
| F.3.3.7 | Equipment with multiple supply connections | | N/A |
| F.3.4 | Voltage setting device | No voltage setting device. | N/A |
| F.3.5 | Terminals and operating devices | | N/A |
| F.3.5.1 | Mains appliance outlet and socket-outlet markings..... : | | N/A |
| F.3.5.2 | Switch position identification marking..... : | | N/A |
| F.3.5.3 | Replacement fuse identification and rating markings..... : | | N/A |
| | Instructional safeguards for neutral fuse..... : | | N/A |
| F.3.5.4 | Replacement battery identification marking..... : | | N/A |
| F.3.5.5 | Neutral conductor terminal | | N/A |
| F.3.5.6 | Terminal marking location | | N/A |
| F.3.6 | Equipment markings related to equipment classification | | N/A |
| F.3.6.1 | Class I equipment | | N/A |
| F.3.6.1.1 | Protective earthing conductor terminal..... : | | N/A |
| F.3.6.1.2 | Protective bonding conductor terminals..... : | | N/A |
| F.3.6.2 | Equipment class marking..... : | | N/A |
| F.3.6.3 | Functional earthing terminal marking..... : | | N/A |
| F.3.7 | Equipment IP rating marking..... : | IPX0 | N/A |
| F.3.8 | External power supply output marking..... : | | N/A |
| F.3.9 | Durability, legibility and permanence of marking | All markings required are easily discernible under normal lighting conditions. | P |
| F.3.10 | Test for permanence of markings | After rubbing test by water and petroleum spirit, the marking still legible; it is not easily possible to remove the marking plate and show no curling. | P |
| F.4 | Instructions | | N/A |
| | a)..... Information prior to installation and initial use | | N/A |
| | b)..... Equipment for use in locations where children not likely to be present | | N/A |
| | c)..... Instructions for installation and interconnection | | N/A |

| IEC 62368-1 | | | |
|-------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | d)..... Equipment intended for use only in restricted access area | | N/A |
| | e)..... Equipment intended to be fastened in place | | N/A |
| | f)..... Instructions for audio equipment terminals | | N/A |
| | g)..... Protective earthing used as a safeguard | | N/A |
| | h)..... Protective conductor current exceeding ES2 limits | | N/A |
| | i)..... Graphic symbols used on equipment | | N/A |
| | j)..... Permanently connected equipment not provided with all-pole mains switch | | N/A |
| | k)..... Replaceable components or modules providing safeguard function | | N/A |
| | l)..... Equipment containing insulating liquid | | N/A |
| | m)..... Installation instructions for outdoor equipment | | N/A |
| F.5 | Instructional safeguards | | P |
| G | COMPONENTS | | P |
| G.1 | Switches | | N/A |
| G.1.1 | General | | N/A |
| G.1.2 | Ratings, endurance, spacing, maximum load | | N/A |
| G.1.3 | Test method and compliance | | N/A |
| G.2 | Relays | | N/A |
| G.2.1 | Requirements | | N/A |
| G.2.2 | Overload test | | N/A |
| G.2.3 | Relay controlling connectors supplying power to other equipment | | N/A |
| G.2.4 | Test method and compliance | | N/A |
| G.3 | Protective devices | | N/A |
| G.3.1 | Thermal cut-offs | | N/A |
| | Thermal cut-outs separately approved according to IEC 60730 with conditions indicated in a) & b) | | N/A |

| IEC 62368-1 | | | |
|-------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Thermal cut-outs tested as part of the equipment as indicated in c) | | N/A |
| G.3.1.2 | Test method and compliance | | N/A |
| G.3.2 | Thermal links | | N/A |
| G.3.2.1 | a) Thermal links tested separately according to IEC 60691 with specifics | | N/A |
| | b) Thermal links tested as part of the equipment | | N/A |
| G.3.2.2 | Test method and compliance | | N/A |
| G.3.3 | PTC thermistors | | N/A |
| G.3.4 | Overcurrent protection devices | | N/A |
| G.3.5 | Safeguards components not mentioned in G.3.1 to G.3.4 | | N/A |
| G.3.5.1 | Non-resettable devices suitably rated and marking provided | | N/A |
| G.3.5.2 | Single faults conditions.....: (See appended table B.3, B.4) | | N/A |
| G.4 | Connectors | | N/A |
| G.4.1 | Spacings | | N/A |
| G.4.2 | Mains connector configuration.....: (See Annex J) | | N/A |
| G.4.3 | Plug is shaped that insertion into mains socket-outlets or appliance coupler is unlikely | | N/A |
| G.5 | Wound components | | N/A |
| G.5.1 | Wire insulation in wound components | (See Annex J) | N/A |
| G.5.1.2 | Protection against mechanical stress | | N/A |
| G.5.2 | Endurance test | | N/A |
| G.5.2.1 | General test requirements | | N/A |
| G.5.2.2 | Heat run test | | N/A |
| | Test time (days per cycle).....: (See Annex J) | | — |
| | Test temperature (°C).....: (See Annex J) | | — |
| G.5.2.3 | Wound components supplied from the mains | | N/A |
| G.5.2.4 | No insulation breakdown | | N/A |
| G.5.3 | Transformers | | N/A |
| G.5.3.1 | Compliance method.....: (See Annex G.5.3.2 and G.5.3.3.) | | N/A |
| | Position.....: (See Annex G.5.3.2 and G.5.3.3.) | | N/A |
| | Method of protection.....: (See Annex G.5.3.2 and G.5.3.3.) | | N/A |
| G.5.3.2 | Insulation | | N/A |
| | Protection from displacement of windings.....: Bobbin and insulation tape | | — |

| IEC 62368-1 | | | |
|-------------|---|-------------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| G.5.3.3 | Transformer overload tests | (See appended table B.3, B.4) | N/A |
| G.5.3.3.1 | Test conditions | | N/A |
| G.5.3.3.2 | Winding temperatures | | N/A |
| G.5.3.3.3 | Winding temperatures - alternative test method | | N/A |
| G.5.3.4 | Transformers using FIW | | N/A |
| G.5.3.4.1 | General | | N/A |
| | FIW wire nominal diameter..... : | | — |
| G.5.3.4.2 | Transformers with basic insulation only | | N/A |
| G.5.3.4.3 | Transformers with double insulation or reinforced insulation..... : | | N/A |
| G.5.3.4.4 | Transformers with FIW wound on metal or ferrite core | | N/A |
| G.5.3.4.5 | Thermal cycling test and compliance | | N/A |
| G.5.3.4.6 | Partial discharge test | | N/A |
| G.5.3.4.7 | Routine test | | N/A |
| G.5.4 | Motors | | P |
| G.5.4.1 | General requirements | | P |
| G.5.4.2 | Motor overload test conditions | | N/A |
| G.5.4.3 | Running overload test | | N/A |
| G.5.4.4.2 | Locked-rotor overload test | | N/A |
| | Test duration (days) : | | — |
| G.5.4.5 | Running overload test for DC motors | | N/A |
| G.5.4.5.2 | Tested in the unit | | N/A |
| G.5.4.5.3 | Alternative method | | N/A |
| G.5.4.6 | Locked-rotor overload test for DC motors | | N/A |
| G.5.4.6.2 | Tested in the unit | | N/A |
| | Maximum Temperature : | (See appended table B.3, B.4) | N/A |
| G.5.4.6.3 | Alternative method | | N/A |
| G.5.4.7 | Motors with capacitors | | N/A |
| G.5.4.8 | Three-phase motors | | N/A |
| G.5.4.9 | Series motors | | N/A |
| | Operating voltage : | | — |
| G.6 | Wire Insulation | | N/A |
| G.6.1 | General | | N/A |
| G.6.2 | Enamelled winding wire insulation | | N/A |
| G.7 | Mains supply cords | | N/A |

| IEC 62368-1 | | | |
|-------------|---|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| G.7.1 | General requirements | | N/A |
| | Type..... : | | — |
| G.7.2 | Cross sectional area (mm ² or AWG)..... : | | N/A |
| G.7.3 | Cord anchorages and strain relief for non-detachable power supply cords | | N/A |
| G.7.3.2 | Cord strain relief | | N/A |
| G.7.3.2.1 | Requirements | | N/A |
| | Strain relief test force (N)..... : | | N/A |
| G.7.3.2.2 | Strain relief mechanism failure | | N/A |
| G.7.3.2.3 | Cord sheath or jacket position, distance (mm)..... : | | N/A |
| G.7.3.2.4 | Strain relief and cord anchorage material | | N/A |
| G.7.4 | Cord Entry | | N/A |
| G.7.5 | Non-detachable cord bend protection | | N/A |
| G.7.5.1 | Requirements | | N/A |
| G.7.5.2 | Test method and compliance | | N/A |
| | Overall diameter or minor overall dimension, <i>D</i> (mm)..... : | | — |
| | Radius of curvature after test (mm)..... : | | — |
| G.7.6 | Supply wiring space | | N/A |
| G.7.6.1 | General requirements | | N/A |
| G.7.6.2 | Stranded wire | | N/A |
| G.7.6.2.1 | Requirements | | N/A |
| G.7.6.2.2 | Test with 8 mm strand | | N/A |
| G.8 | Varistors | | N/A |
| G.8.1 | General requirements | | N/A |
| G.8.2 | Safeguards against fire | | N/A |
| G.8.2.1 | General | | N/A |
| G.8.2.2 | Varistor overload test | | N/A |
| G.8.2.3 | Temporary overvoltage test | | N/A |
| G.9 | Integrated circuit (IC) current limiters | | N/A |
| G.9.1 | Requirements | | N/A |
| | IC limiter output current (max. 5A)..... : | | — |
| | Manufacturers' defined drift : | | — |
| G.9.2 | Test Program | | N/A |
| G.9.3 | Compliance | | N/A |
| G.10 | Resistors | | N/A |

| IEC 62368-1 | | | |
|-------------|---|-------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| G.10.1 | General | | N/A |
| G.10.2 | Conditioning | | N/A |
| G.10.3 | Resistor test | | N/A |
| G.10.4 | Voltage surge test | | N/A |
| G.10.5 | Impulse test | | N/A |
| G.10.6 | Overload test | | N/A |
| G.11 | Capacitors and RC units | | N/A |
| G.11.1 | General requirements | | N/A |
| G.11.2 | Conditioning of capacitors and RC units | | N/A |
| G.11.3 | Rules for selecting capacitors | | N/A |
| G.12 | Optocouplers | | N/A |
| | Optocouplers comply with IEC 60747-5-5 with specifics | | N/A |
| | Type test voltage $V_{ini, a}$: | | — |
| | Routine test voltage, $V_{ini, b}$: | | — |
| G.13 | Printed boards | | P |
| G.13.1 | General requirements | | P |
| G.13.2 | Uncoated printed boards | | P |
| G.13.3 | Coated printed boards | | N/A |
| G.13.4 | Insulation between conductors on the same inner surface | | P |
| G.13.5 | Insulation between conductors on different surfaces | | N/A |
| | Distance through insulation..... : | | N/A |
| | Number of insulation layers (pcs) : | | — |
| G.13.6 | Tests on coated printed boards | | N/A |
| G.13.6.1 | Sample preparation and preliminary inspection | | N/A |
| G.13.6.2 | Test method and compliance | | N/A |
| G.14 | Coating on components terminals | | N/A |
| G.14.1 | Requirements : | (See Clause G.13) | N/A |
| G.15 | Pressurized liquid filled components | | N/A |
| G.15.1 | Requirements | | N/A |
| G.15.2 | Test methods and compliance | | N/A |
| G.15.2.1 | Hydrostatic pressure test | | N/A |
| G.15.2.2 | Creep resistance test | | N/A |
| G.15.2.3 | Tubing and fittings compatibility test | | N/A |
| G.15.2.4 | Vibration test | | N/A |

| IEC 62368-1 | | | |
|----------------|--|-----------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| G.15.2.5 | Thermal cycling test | | N/A |
| G.15.2.6 | Force test | | N/A |
| G.15.3 | Compliance | | N/A |
| G.16 | IC including capacitor discharge function (ICX) | | N/A |
| G.16.1 | Condition for fault tested is not required | | N/A |
| | ICX with associated circuitry tested in equipment | | N/A |
| | ICX tested separately | | N/A |
| G.16.2 | Tests | | N/A |
| | Smallest capacitance and smallest resistance specified by ICX manufacturer for impulse test..... : | | — |
| | Mains voltage that impulses to be superimposed on : | | — |
| | Largest capacitance and smallest resistance for ICX tested by itself for 10000 cycles test..... : | | — |
| G.16.3 | Capacitor discharge test..... : | | N/A |
| H | CRITERIA FOR TELEPHONE RINGING SIGNALS | | N/A |
| H.1 | General | | N/A |
| H.2 | Method A | | N/A |
| H.3 | Method B | | N/A |
| H.3.1 | Ringling signal | | N/A |
| H.3.1.1 | Frequency (Hz) : | | — |
| H.3.1.2 | Voltage (V) : | | — |
| H.3.1.3 | Cadence; time (s) and voltage (V) : | | — |
| H.3.1.4 | Single fault current (mA):..... : | | — |
| H.3.2 | Tripping device and monitoring voltage | | N/A |
| H.3.2.1 | Conditions for use of a tripping device or a monitoring voltage | | N/A |
| H.3.2.2 | Tripping device | | N/A |
| H.3.2.3 | Monitoring voltage (V)..... : | | N/A |
| J | INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION | | N/A |
| J.1 | General | | N/A |
| | Winding wire insulation..... : | (See appended table 4.1.2.) | — |
| | Solid round winding wire, diameter (mm)..... : | | N/A |
| | Solid square and rectangular (flatwise bending) winding wire, cross-sectional area (mm ²)..... : | | N/A |
| J.2/J.3 | Tests and Manufacturing | (See separate test report) | N/A |

| IEC 62368-1 | | | |
|-------------|--|----------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| K | SAFETY INTERLOCKS | | N/A |
| K.1 | General requirements | | N/A |
| | Instructional safeguard..... : | | N/A |
| K.2 | Components of safety interlock safeguard mechanism | | N/A |
| K.3 | Inadvertent change of operating mode | | N/A |
| K.4 | Interlock safeguard override | | N/A |
| K.5 | Fail-safe | | N/A |
| K.5.1 | Under single fault condition | | N/A |
| K.6 | Mechanically operated safety interlocks | | N/A |
| K.6.1 | Endurance requirement | | N/A |
| K.6.2 | Test method and compliance..... : | | N/A |
| K.7 | Interlock circuit isolation | | N/A |
| K.7.1 | Separation distance for contact gaps & interlock circuit elements | | N/A |
| | In circuit connected to mains, separation distance for contact gaps (mm)..... : | | N/A |
| | In circuit isolated from mains, separation distance for contact gaps (mm)..... : | | N/A |
| | Electric strength test before and after the test of K.7.2..... : | (See appended table 5.4.9) | N/A |
| K.7.2 | Overload test, Current (A)..... : | | N/A |
| K.7.3 | Endurance test | | N/A |
| K.7.4 | Electric strength test | | N/A |
| L | DISCONNECT DEVICES | | N/A |
| L.1 | General requirements | | N/A |
| L.2 | Permanently connected equipment | | N/A |
| L.3 | Parts that remain energized | | N/A |
| L.4 | Single-phase equipment | | N/A |
| L.5 | Three-phase equipment | | N/A |
| L.6 | Switches as disconnect devices | | N/A |
| L.7 | Plugs as disconnect devices | | N/A |
| L.8 | Multiple power sources | | N/A |
| | Instructional safeguard..... : | | N/A |
| M | EQUIPMENT CONTAINING BATTERIES AND THEIR PROTECTION CIRCUITS | | P |
| M.1 | General requirements | | P |
| M.2 | Safety of batteries and their cells | | P |

| IEC 62368-1 | | | |
|-------------|--|---|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| M.2.1 | Batteries and their cells comply with relevant IEC standards..... : | Approved battery used | P |
| M.3 | Protection circuits for batteries provided within the equipment | | P |
| M.3.1 | Requirements | | P |
| M.3.2 | Test method | | P |
| | Overcharging of a rechargeable battery | (See appended table Annex M) | P |
| | Excessive discharging | (See appended table Annex M) | P |
| | Unintentional charging of a non-rechargeable battery | | N/A |
| | Reverse charging of a rechargeable battery | | N/A |
| M.3.3 | Compliance | (See appended table M.3) | P |
| M.4 | Additional safeguards for equipment containing a portable secondary lithium battery | | P |
| M.4.1 | General | | P |
| M.4.2 | Charging safeguards | | P |
| M.4.2.1 | Requirements | | P |
| M.4.2.2 | Compliance..... : | (See appended table M.4.2) | P |
| M.4.3 | Fire enclosure..... : | | N/A |
| M.4.4 | Drop test of equipment containing a secondary lithium battery | | P |
| M.4.4.2 | Preparation and procedure for the drop test | | P |
| M.4.4.3 | Drop, Voltage on reference and dropped batteries (V); voltage difference during 24 h period (%): | | P |
| M.4.4.4 | Check of the charge/discharge function | | P |
| M.4.4.5 | Charge / discharge cycle test | | P |
| M.4.4.6 | Compliance | | P |
| M.5 | Risk of burn due to short-circuit during carrying | | N/A |
| M.5.1 | Requirement | | N/A |
| M.5.2 | Test method and compliance | | N/A |
| M.6 | Safeguards against short-circuits | | P |
| M.6.1 | External and internal faults | | P |
| M.6.2 | Compliance | Has been conducted on the battery as part of compliance with IEC 62133-2. | P |
| M.7 | Risk of explosion from lead acid and NiCd batteries | | N/A |
| M.7.1 | Ventilation preventing explosive gas concentration | | N/A |

| IEC 62368-1 | | | |
|-------------|---|------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Calculated hydrogen generation rate..... : | | N/A |
| M.7.2 | Test method and compliance | | N/A |
| | Minimum air flow rate, Q (m ³ /h)..... : | | N/A |
| M.7.3 | Ventilation tests | | N/A |
| M.7.3.1 | General | | N/A |
| M.7.3.2 | Ventilation test – alternative 1 | | N/A |
| | Hydrogen gas concentration (%)..... : | | N/A |
| M.7.3.3 | Ventilation test – alternative 2 | | N/A |
| | Obtained hydrogen generation rate..... : | | N/A |
| M.7.3.4 | Ventilation test – alternative 3 | | N/A |
| | Hydrogen gas concentration (%)..... : | | N/A |
| M.7.4 | Marking..... : | | N/A |
| M.8 | Protection against internal ignition from external spark sources of batteries with aqueous electrolyte | | N/A |
| M.8.1 | General | | N/A |
| M.8.2 | Test method | | N/A |
| M.8.2.1 | General | | N/A |
| M.8.2.2 | Estimation of hypothetical volume V_z (m ³ /s)..... : | | — |
| M.8.2.3 | Correction factors..... : | | — |
| M.8.2.4 | Calculation of distance d (mm) : | | — |
| M.9 | Preventing electrolyte spillage | | N/A |
| M.9.1 | Protection from electrolyte spillage | | N/A |
| M.9.2 | Tray for preventing electrolyte spillage | | N/A |
| M.10 | Instructions to prevent reasonably foreseeable misuse | Stated in user manual. | P |
| | Instructional safeguard..... : | | P |
| N | ELECTROCHEMICAL POTENTIALS | | N/A |
| | Material(s) used..... : | | — |
| O | MEASUREMENT OF CREEPAGE DISTANCES AND CLEARANCES | | N/A |
| | Value of X (mm)..... : | | — |
| P | SAFEGUARDS AGAINST CONDUCTIVE OBJECTS | | N/A |
| P.1 | General | | N/A |
| P.2 | Safeguards against entry or consequences of entry of a foreign object | | N/A |
| P.2.1 | General | | N/A |
| P.2.2 | Safeguards against entry of a foreign object | | N/A |
| | Location and Dimensions (mm) : | | — |

| IEC 62368-1 | | | |
|-------------|---|--------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| P.2.3 | Safeguards against the consequences of entry of a foreign object | | N/A |
| P.2.3.1 | Safeguard requirements | | N/A |
| | The ES3 and PS3 keep-out volume in Figure P.3 not applicable to transportable equipment | | N/A |
| | Transportable equipment with metalized plastic parts..... : | | N/A |
| P.2.3.2 | Consequence of entry test..... : | | N/A |
| P.3 | Safeguards against spillage of internal liquids | | N/A |
| P.3.1 | General | | N/A |
| P.3.2 | Determination of spillage consequences | | N/A |
| P.3.3 | Spillage safeguards | | N/A |
| P.3.4 | Compliance | | N/A |
| P.4 | Metallized coatings and adhesives securing parts | | N/A |
| P.4.1 | General | | N/A |
| P.4.2 | Tests | | N/A |
| | Conditioning, T _c (°C)..... : | | — |
| | Duration (weeks)..... : | | — |
| Q | CIRCUITS INTENDED FOR INTERCONNECTION WITH BUILDING WIRING | | N/A |
| Q.1 | Limited power sources | | N/A |
| Q.1.1 | Requirements | | N/A |
| | a) Inherently limited output | (See appended table Q.1) | N/A |
| | b) Impedance limited output | | N/A |
| | c) Regulating network limited output | (See appended table Q.1) | N/A |
| | d) Overcurrent protective device limited output | | N/A |
| | e) IC current limiter complying with G.9 | | N/A |
| Q.1.2 | Test method and compliance..... : | (See appended table Q.1) | N/A |
| | Current rating of overcurrent protective device (A) : | | N/A |
| Q.2 | Test for external circuits – paired conductor cable | | N/A |
| | Maximum output current (A) : | | N/A |
| | Current limiting method..... : | | — |
| R | LIMITED SHORT CIRCUIT TEST | | N/A |
| R.1 | General | | N/A |
| R.2 | Test setup | | N/A |
| | Overcurrent protective device for test..... : | | — |

| IEC 62368-1 | | | |
|-------------|---|--------------------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| R.3 | Test method | | N/A |
| | Cord/cable used for test..... : | | — |
| R.4 | Compliance | | N/A |
| S | TESTS FOR RESISTANCE TO HEAT AND FIRE | | N/A |
| S.1 | Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power does not exceed 4 000 W | | N/A |
| | Samples, material..... : | | — |
| | Wall thickness (mm)..... : | | — |
| | Conditioning (°C)..... : | | — |
| | Test flame according to IEC 60695-11-5 with conditions as set out | | N/A |
| | - Material not consumed completely | | N/A |
| | - Material extinguishes within 30s | | N/A |
| | - No burning of layer or wrapping tissue | | N/A |
| S.2 | Flammability test for fire enclosure and fire barrier integrity | | N/A |
| | Samples, material..... : | | — |
| | Wall thickness (mm)..... : | | — |
| | Conditioning (°C)..... : | | — |
| S.3 | Flammability test for the bottom of a fire enclosure | | N/A |
| S.3.1 | Mounting of samples | | N/A |
| S.3.2 | Test method and compliance | | N/A |
| | Mounting of samples : | | — |
| | Wall thickness (mm)..... : | | — |
| S.4 | Flammability classification of materials | | N/A |
| S.5 | Flammability test for fire enclosures and fire barrier materials of equipment where the steady state power exceeding 4 000 W | | N/A |
| | Samples, material..... : | | — |
| | Wall thickness (mm)..... : | | — |
| | Conditioning (°C)..... : | | — |
| T | MECHANICAL STRENGTH TESTS | | P |
| T.1 | General | | P |
| T.2 | Steady force test, 10 N : | (See appended table T.2) | N/A |
| T.3 | Steady force test, 30 N : | | N/A |
| T.4 | Steady force test, 100 N : | (See appended table T.4) | P |
| T.5 | Steady force test, 250 N : | (See appended table T.5) | N/A |
| T.6 | Enclosure impact test | | N/A |

| IEC 62368-1 | | | |
|-------------|---|--|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| | Fall test | | N/A |
| | Swing test | | N/A |
| T.7 | Drop test | (See appended table T.7) | P |
| T.8 | Stress relief test | (See appended table T.8) | P |
| T.9 | Glass Impact Test | | N/A |
| T.10 | Glass fragmentation test | | N/A |
| | Number of particles counted..... | No such glass provided. | N/A |
| T.11 | Test for telescoping or rod antennas | | N/A |
| | Torque value (Nm) | No such antennas provided. | N/A |
| U | MECHANICAL STRENGTH OF CATHODE RAY TUBES (CRT) AND PROTECTION AGAINST THE EFFECTS OF IMPLOSION | | N/A |
| U.1 | General | | N/A |
| | Instructional safeguard : | | N/A |
| U.2 | Test method and compliance for non-intrinsically protected CRTs | | N/A |
| U.3 | Protective screen | | N/A |
| V | DETERMINATION OF ACCESSIBLE PARTS | | N/A |
| V.1 | Accessible parts of equipment | | N/A |
| V.1.1 | General | Following the probes test specified in this annex Figure V.1, V.2, V.5 are suitable. | N/A |
| V.1.2 | Surfaces and openings tested with jointed test probes | | N/A |
| V.1.3 | Openings tested with straight unjointed test probes | | N/A |
| V.1.4 | Plugs, jacks, connectors tested with blunt probe | | N/A |
| V.1.5 | Slot openings tested with wedge probe | | N/A |
| V.1.6 | Terminals tested with rigid test wire | | N/A |
| V.2 | Accessible part criterion | | N/A |
| X | ALTERNATIVE METHOD FOR DETERMINING CLEARANCES FOR INSULATION IN CIRCUITS CONNECTED TO AN AC MAINS NOT EXCEEDING 420 V PEAK (300 V RMS) | | N/A |
| | Clearance..... | (See appended table X) | N/A |
| Y | CONSTRUCTION REQUIREMENTS FOR OUTDOOR ENCLOSURES | | N/A |
| Y.1 | General | | N/A |
| Y.2 | Resistance to UV radiation | | N/A |
| Y.3 | Resistance to corrosion | | N/A |
| Y.3.1 | Metallic parts of outdoor enclosures are resistant to effects of water-borne contaminants by..... | | N/A |

| IEC 62368-1 | | | |
|-------------|--|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |
| Y.3.2 | Test apparatus | | N/A |
| Y.3.3 | Water – saturated sulphur dioxide atmosphere | | N/A |
| Y.3.4 | Test procedure..... : | | N/A |
| Y.3.5 | Compliance | | N/A |
| Y.4 | Gaskets | | N/A |
| Y.4.1 | General | | N/A |
| Y.4.2 | Gasket tests | | N/A |
| Y.4.3 | Tensile strength and elongation tests | | N/A |
| | Alternative test methods..... : | | N/A |
| Y.4.4 | Compression test | | N/A |
| Y.4.5 | Oil resistance | | N/A |
| Y.4.6 | Securing means | (See Annex P.4) | N/A |
| Y.5 | Protection of equipment within an outdoor enclosure | | N/A |
| Y.5.1 | General | | N/A |
| Y.5.2 | Protection from moisture | | N/A |
| | Relevant tests of IEC 60529 or Y.5.3..... : | | N/A |
| Y.5.3 | Water spray test | | N/A |
| Y.5.4 | Protection from plants and vermin | | N/A |
| Y.5.5 | Protection from excessive dust | | N/A |
| Y.5.5.1 | General | | N/A |
| Y.5.5.2 | IP5X equipment | | N/A |
| Y.5.5.3 | IP6X equipment | | N/A |
| Y.6 | Mechanical strength of enclosures | | N/A |
| Y.6.1 | General | | N/A |
| Y.6.2 | Impact test..... : | (See Table T.6) | N/A |

| IEC 62368-1 | | | | | | | |
|---|---|-----------------|------------|-----------------|--------------------|-------------------------------|----------|
| Clause | Requirement + Test | | | Result - Remark | | | Verdict |
| 5.2 | TABLE: Classification of electrical energy sources | | | | | | P |
| Supply Voltage | Location (e.g. circuit designation) | Test conditions | Parameters | | | | ES Class |
| | | | U (V) | I (mA) | Type ¹⁾ | Additional Info ²⁾ | |
| 5Vdc | Input circuit | Normal | 5Vdc | -- | SS | -- | ES1 |
| Supplementary information: 1) Type: Steady state (SS), Capacitance (CP), Single pulse (SP), Repetitive pulses (RP), etc. 2) Additional Info: Frequency, Pulse duration, Pulse off time, Capacitance value, etc. | | | | | | | |

| 5.4.1.8 | TABLE: Working voltage measurement | | | | N/A |
|----------------------------|---|-----------------|------------------|----------------|----------|
| Location | | RMS voltage (V) | Peak voltage (V) | Frequency (Hz) | Comments |
| -- | | -- | -- | -- | -- |
| Supplementary information: | | | | | |

| 5.4.1.10.2 | TABLE: Vicat softening temperature of thermoplastics | | | N/A |
|-------------------------------|---|----------------|------------------|-----|
| Method..... : | | | ISO 306 / B50 | — |
| Object/ Part No./Material | Manufacturer/trademark | Thickness (mm) | T softening (°C) | |
| -- | -- | -- | -- | |
| Supplementary information: -- | | | | |

| 5.4.1.10.3 | TABLE: Ball pressure test of thermoplastics | | | | N/A |
|---|--|----------------|-----------------------|--------------------------|-----|
| Allowed impression diameter (mm)..... : | | | | ≤ 2 mm | — |
| Object/Part No./Material | Manufacturer/trademark | Thickness (mm) | Test temperature (°C) | Impression diameter (mm) | |
| -- | -- | -- | -- | -- | |
| Supplementary information: -- | | | | | |

| 5.4.2, 5.4.3 | TABLE: Minimum Clearances/Creepage distance | | | | | | | N/A |
|---|--|----------------------|-------------------------|------------------|---------|------------------------|------------------|---------|
| Clearance (cl) and creepage distance (cr) at/of/between: | U _p (V) | U _{rms} (V) | Freq ¹⁾ (Hz) | Required cl (mm) | cl (mm) | E.S. ²⁾ (V) | Required cr (mm) | cr (mm) |
| -- | -- | -- | -- | -- | -- | -- | -- | -- |
| Supplementary information: 1) Only for frequency above 30 kHz 2) Complete Electric Strength voltage (E.S. (V) when 5.4.2.4 applied) | | | | | | | | |

| IEC 62368-1 | | | | |
|---|---|-----------------|-------------------|-------------------|
| Clause | Requirement + Test | Result - Remark | Verdict | |
| 5.4.4.2 | TABLE: Minimum distance through insulation | | | N/A |
| Distance through insulation (DTI) at/of | Peak voltage (V) | Insulation | Required DTI (mm) | Measured DTI (mm) |
| -- | -- | -- | -- | -- |
| Supplementary information: -- | | | | |

| 5.4.4.9 | TABLE: Solid insulation at frequencies >30 kHz | | | | | N/A |
|-------------------------------|--|-----------------|-------|--------------------|------------|----------------|
| Insulation material | E_p | Frequency (kHz) | K_R | Thickness d (mm) | Insulation | V_{PW} (Vpk) |
| -- | -- | -- | -- | -- | -- | -- |
| Supplementary information: -- | | | | | | |

| 5.4.9 | TABLE: Electric strength tests | | | N/A |
|-------------------------------|--|------------------|--------------------|-----|
| Test voltage applied between: | Voltage shape (Surge, Impulse, AC, DC, etc.) | Test voltage (V) | Breakdown Yes / No | |
| -- | -- | -- | -- | |
| Supplementary information: -- | | | | |

| 5.5.2.2 | TABLE: Stored discharge on capacitors | | | | N/A |
|---|--|---|-----------------|------------------------|----------|
| Location | Supply voltage (V) | Operating and fault condition ¹⁾ | Switch position | Measured voltage (Vpk) | ES Class |
| -- | -- | Normal condition | -- | -- | -- |
| Supplementary information: X-capacitors installed for testing: <input type="checkbox"/> bleeding resistor rating: <input type="checkbox"/> ICX: 1) Normal operating condition (e.g., normal operation, or open fuse), SC= short circuit, OC= open circuit | | | | | |

| 5.6.6 | TABLE: Resistance of protective conductors and terminations | | | | N/A |
|-------------------------------|--|----------------|------------------|-------------------------|-----|
| Location | Test current (A) | Duration (min) | Voltage drop (V) | Resistance (Ω) | |
| -- | -- | -- | -- | -- | |
| Supplementary information: -- | | | | | |

| 5.7.4 | TABLE: Unearthed accessible parts | | | N/A |
|--------------|--|--------|------------|-----|
| Location | Operating and | Supply | Parameters | ES |
| | | | | |

| IEC 62368-1 | | | | | | |
|---|--------------------|-------------|--|--|------------|---------|
| Clause | Requirement + Test | | | Result - Remark | | Verdict |
| | fault conditions | Voltage (V) | Voltage (V _{rms} or V _{pk}) | Current (A _{rms} or A _{pk}) | Freq. (Hz) | class |
| -- | -- | -- | -- | -- | -- | -- |
| Supplementary information: Abbreviation: SC= short circuit; OC= open circuit | | | | | | |

| 5.7.5 | TABLE: Earthed accessible conductive part | | | | | N/A |
|---------------------------------|---|---|--------------------|---------|--|-----|
| Supply voltage (V).....: | | | | | | — |
| Phase(s) | | [] Single Phase; [] Three Phase: [] Delta [] Wye | | | | |
| Power Distribution System | | <input type="checkbox"/> TN <input type="checkbox"/> TT <input type="checkbox"/> IT | | | | |
| Location | | Fault Condition No in IEC 60990 clause 6.2.2 | Touch current (mA) | Comment | | |
| -- | | -- | -- | -- | | |
| Supplementary Information: -- | | | | | | |

| 5.8 | TABLE: Backfeed safeguard in battery backed up supplies | | | | | N/A |
|---|---|-------------------------------|----------|--------------------------|-------------------|----------|
| Location | Supply voltage (V) | Operating and fault condition | Time (s) | Open-circuit voltage (V) | Touch current (A) | ES Class |
| -- | -- | -- | -- | -- | -- | -- |
| Supplementary information: Abbreviation: SC= short circuit, OC= open circuit | | | | | | |

| 6.2.2 | TABLE: Power source circuit classifications | | | | | P |
|--|---|-------------|-------------|------------------------------|----------|----------|
| Location | Operating and fault condition | Voltage (V) | Current (A) | Max. Power ¹⁾ (W) | Time (S) | PS class |
| Input | Normal condition | 5Vdc | 1.82 | 9.10 | 3 | PS1 |
| Li-ion battery | Normal condition | 3.40 | 7.35 | 24.99 | 5 | PS2 |
| | Q1 pin 1 – 3 SC | 3.37 | 7.73 | 26.05 | 5 | PS2 |
| Supplementary information: Abbreviation: SC= short circuit; OC= open circuit 1) Measured after 3 s for PS1 and measured after 5 s for PS2 and PS3. | | | | | | |

| 6.2.3.1 | TABLE: Determination of Arcing PIS | | | | N/A |
|----------|--------------------------------------|----------------------------|------------------|----------------------|-----|
| Location | Open circuit voltage after 3 s (Vpk) | Measured r.m.s current (A) | Calculated value | Arcing PIS? Yes / No | |

| IEC 62368-1 | | | | |
|-------------------------------|--------------------|-----------------|----|---------|
| Clause | Requirement + Test | Result - Remark | | Verdict |
| -- | -- | -- | -- | -- |
| Supplementary information: -- | | | | |

| 6.2.3.2 | TABLE: Determination of resistive PIS | | | P |
|---|---------------------------------------|---------------------|----------------------------|---|
| Location | Operating and fault condition | Dissipate power (W) | Resistive PIS? Yes / No | |
| All circuits within equipment | -- | -- | Yes (declaration) | |
| Supplementary information: Abbreviation: SC= short circuit; OC= open circuit | | | | |

| 8.5.5 | TABLE: High pressure lamp | | | | N/A |
|-------------------------------|---------------------------|------------------|-------------------------------------|---------------------------------------|-----|
| Lamp manufacturer | Lamp type | Explosion method | Longest axis of glass particle (mm) | Particle found beyond 1 m Yes / No | |
| -- | -- | -- | -- | -- | |
| Supplementary information: -- | | | | | |

| 9.6 | TABLE: Temperature measurements for wireless power transmitters | | | | | | | | N/A |
|---|---|--------------|----------------------------------|--------------|---------------------------------------|--------------|---------------------------------------|--------------|-----|
| Supply voltage (V)..... | | -- | | | | | | — | |
| Max. transmit power of transmitter (W)..... | | -- | | | | | | — | |
| Foreign objects | w/o receiver and direct contact | | with receiver and direct contact | | with receiver and at distance of 2 mm | | with receiver and at distance of 5 mm | | |
| | Object (°C) | Ambient (°C) | Object (°C) | Ambient (°C) | Object (°C) | Ambient (°C) | Object (°C) | Ambient (°C) | |
| -- | -- | -- | -- | -- | -- | -- | -- | -- | |
| Supplementary information: -- | | | | | | | | | |

| 5.4.1.4, 9.3, B.1.5, B.2.6 | TABLE: Temperature measurements | | | | P |
|---|---------------------------------|----------------------------|--------------------------------------|------------------------|---|
| Supply voltage (V)..... | 5Vdc (charging mode) | 3.85Vdc (discharging mode) | 5Vdc (charging and discharging mode) | — | |
| Ambient temperature during test T_{amb} (°C)..... | 25.0 | 25.0 | 25.0 | — | |
| Maximum measured temperature T of part/at: | T (°C) | | | Allowed T_{max} (°C) | |
| Type-C input port (metal) | 32.2 | 28.6 | 34.6 | 130 | |

| IEC 62368-1 | | | | | | | |
|-------------------------------------|---------------------|--------------------|---------------------|--------------------|-----------------|-------------------------------|------------------|
| Clause | Requirement + Test | | | | Result - Remark | | Verdict |
| PCB near U0500 | 40.5 | | | | 39.2 | 47.8 | 130 |
| PCB near U0013 | 38.4 | | | | 44.6 | 50.0 | 130 |
| Internal wire | 32.6 | | | | 45.1 | 43.5 | 80 |
| Li-ion battery surface | 32.8 | | | | 34.8 | 35.6 | Ref. |
| Inside of metal enclosure near PCB | 35.4 | | | | 38.2 | 42.2 | Ref. |
| Outside of metal enclosure near PCB | 33.2 | | | | 36.4 | 38.8 | 48 |
| LED display screen | 28.6 | | | | 31.2 | 32.6 | 71 |
| Button body | 26.4 | | | | 27.5 | 28.2 | -- |
| Temperature T of winding: | t ₁ (°C) | R ₁ (Ω) | t ₂ (°C) | R ₂ (Ω) | T (°C) | Allowed T _{max} (°C) | Insulation class |
| -- | -- | -- | -- | -- | -- | -- | -- |
| Supplementary information: -- | | | | | | | |

| B.2.5 TABLE: Input test | | | | | | | | P |
|-------------------------------|----|-------|-------------|-------|-------------|---------|------------|------------------|
| U (V) | Hz | I (A) | I rated (A) | P (W) | P rated (W) | Fuse No | I fuse (A) | Condition/status |
| 5Vdc | -- | 1.82 | 2.0 | 9.10 | -- | -- | -- | Normal operation |
| Supplementary information: -- | | | | | | | | |

| B.3, B.4 TABLE: Abnormal operating and fault condition tests | | | | | | | P |
|--|------------------|--------------------|-----------|----------|------------------|--|---|
| Ambient temperature T _{amb} (°C)..... | | | | | | 25°C if not specified | — |
| Power source for EUT: Manufacturer, model/type, output rating..: | | | | | | -- | — |
| Component No. | Condition | Supply voltage (V) | Test time | Fuse no. | Fuse current (A) | Observation | |
| Battery “+” “-” | Over charging | 5.0Vdc | 7hrs | -- | -- | Papper & tissue do not ignite without emitting, no damage, no hazard | |
| Battery “+” “-” | Over discharging | 3.85Vdc | 7hrs | -- | -- | Papper & tissue do not ignite without emitting, no damage, no hazard | |
| Speaker | SC | 5.0Vdc | 10mins | -- | -- | Speaker without output, , similar normal operation, recoverable, no damage, no hazard. | |
| Supplementary information: SC= short circuit; OC= open circuit; | | | | | | | |

| M.3 | TABLE: Protection circuits for batteries provided within the equipment | P |
|-----|--|---|
|-----|--|---|

| IEC 62368-1 | | | |
|-------------|--------------------|-----------------|---------|
| Clause | Requirement + Test | Result - Remark | Verdict |

| | | | | | | |
|---|----------------------------|------------------------------------|-------------|------------------------|-------------------------|------------------------------|
| Is it possible to install the battery in a reverse polarity position?.....: | | -- | --- | | | |
| Equipment Specification | Charging | | | | | |
| | Voltage (V) | | Current (A) | | | |
| -- | 5.0Vdc | | 2.0 | | | |
| Manufacturer/type | Battery specification | | | | | |
| | Non-rechargeable batteries | | | Rechargeable batteries | | |
| | Discharging current (A) | Unintentional charging current (A) | Charging | | Discharging current (A) | Reverse charging current (A) |
| | | | Voltage (V) | Current (A) | | |
| Battery | -- | -- | 5.0Vdc | 4.0 | 4.0 | -- |

Note: The tests of M.3.2 are applicable only when above appropriate data is not available.

| | |
|--|----|
| Specified battery temperature (°C).....: | -- |
|--|----|

| Component No. | Fault condition | Charge/ discharge mode | Test time | Temp. (°C) | Current (A) | Voltage (V) | Observation |
|---------------|-----------------|------------------------|-----------|------------|-------------|-------------|-------------------------------------|
| Battery | Normal | Charge mode | 7h | 35.6°C | 1.70 | 5.0Vdc | Normal work, no damage, no hazards. |
| | | Discharge mode | 7h | 34.8°C | 0.88 | 4.4Vdc | Normal work, no damage, no hazards. |
| | Q1 pin 1-3 SC | Charge mode | 7h | 37.3°C | 1.76 | 5.0Vdc | Normal work, no damage, no hazards. |
| | | Discharge mode | 7h | 36.6°C | 0.92 | 4.4Vdc | Normal work, no damage, no hazards. |

Supplementary information:

Abbreviation: SC= short circuit; OC= open circuit; NL= no chemical leakage; NS= no spillage of liquid; NE= no explosion; NF= no emission of flame or expulsion of molten metal.

| | | | | | | |
|---|--|----------------------|----------------------|--|------------|-------------|
| M.4.2 | TABLE: Charging safeguards for equipment containing a secondary lithium battery | | | | | P |
| Maximum specified charging voltage (V).....: | | | | | 4.4Vdc | --- |
| Maximum specified charging current (A) | | | | | 4.0 | --- |
| Highest specified charging temperature (°C) | | | | | 55 | --- |
| Lowest specified charging temperature (°C) | | | | | 0 | --- |
| Battery manufacturer/type | Operating and fault condition | Measurement | | | Temp. (°C) | Observation |
| | | Charging voltage (V) | Charging current (A) | | | |

| IEC 62368-1 | | | | | | | |
|---|--------------------|--------|------|-----------------|--|---------|--|
| Clause | Requirement + Test | | | Result - Remark | | Verdict | |
| Battery | Charge mode | 4.4Vdc | 0.01 | 0 | Charging normally, not exceed 4.0A. No explosion, no fire, no leakage. | | |
| | | -- | -- | -- | The battery cannot reach 55°C under any condition | | |
| Supplementary information: Abbreviation: SC= short circuit; OC= open circuit; MSCV= maximum specified charging voltage; MSCC= maximum specified charging current; HSCT= highest specified charging temperature; LSCT= lowest specified charging temperature. | | | | | | | |

| Q.1 | TABLE: Circuits intended for interconnection with building wiring (LPS) | | | | | | N/A | |
|---|---|---------------------|----------|---------------------|-------|--------|-------|--|
| Output Circuit | Condition | U _{oc} (V) | Time (s) | I _{sc} (A) | | S (VA) | | |
| | | | | Meas. | Limit | Meas. | Limit | |
| -- | Normal | -- | 5s | -- | 8 | -- | 100 | |
| | Abnormal: overload | -- | 5s | -- | 8 | -- | 100 | |
| | Single fault – SC: | -- | 5s | -- | 8 | -- | 100 | |
| Supplementary Information: *Unit output shut down SC=Short circuit, OC=Open circuit | | | | | | | | |

| T.2, T.3, T.4, T.5 | TABLE: Steady force test | | | | | | P |
|--|--------------------------|----------------|-------|-----------|-------------------|----------------------|---|
| Part/Location | Material | Thickness (mm) | Probe | Force (N) | Test Duration (s) | Observation | |
| Top enclosure | Metal | Min. 1.0 | -- | 100 | 5 | No damage,no hazard. | |
| Side enclosure | Metal | Min. 1.0 | -- | 100 | 5 | No damage,no hazard. | |
| Bottom enclosure | Metal | Min. 1.0 | -- | 100 | 5 | No damage,no hazard. | |
| Supplementary information: 1) See table 4.1.2 | | | | | | | |

| T.6, T.9 | TABLE: Impact test | | | | N/A |
|-------------------------------|--------------------|----------------|-------------|-------------|-----|
| Location/part | Material | Thickness (mm) | Height (mm) | Observation | |
| -- | -- | -- | -- | -- | |
| Supplementary information: -- | | | | | |

| | | | |
|-------------|--------------------|-----------------|---------|
| IEC 62368-1 | | | |
| Clause | Requirement + Test | Result - Remark | Verdict |

| T.7 | TABLE: Drop test | | | | P |
|--|-------------------------|----------------|-------------|----------------------|---|
| Location/part | Material | Thickness (mm) | Height (mm) | Observation | |
| Top enclosure | Metal | Min. 1.0 | 1000 | No damage,no hazard. | |
| Side enclosure | Metal | Min. 1.0 | 1000 | No damage,no hazard. | |
| Bottom enclosure | Metal | Min. 1.0 | 1000 | No damage,no hazard. | |
| Supplementary information: 1) See table 4.1.2 | | | | | |

| T.8 | TABLE: Stress relief test | | | | P |
|--|----------------------------------|-----------------|-----------------------|--------------|--------------------------|
| Location/Part | Material | Thickness (mm) | Oven Temperature (°C) | Duration (h) | Observation |
| Completed sample | Metal/Plastic | See table 4.1.2 | 70 | 7 | No distortion, no hazard |
| Supplementary information: 1) See table 4.1.2 | | | | | |

| X | TABLE: Alternative method for determining minimum clearances distances | | | N/A |
|-------------------------------|---|------------------|------------------|-----|
| Clearance distanced between: | Peak of working voltage (V) | Required cl (mm) | Measured cl (mm) | |
| -- | -- | -- | -- | |
| Supplementary information: -- | | | | |

| | | | |
|-------------|--------------------|-----------------|---------|
| IEC 62368-1 | | | |
| Clause | Requirement + Test | Result - Remark | Verdict |

| 4.1.2 TABLE: List of critical components | | | | | P |
|--|---|-----------------|--|-----------------|---|
| Object / part No. | Manufacturer/ trademark | Type / model | Technical data | Standard | Mark(s) of conformity ¹ |
| Plastic | Interchangeable | Interchangeable | V-0, thickness: 1.0 mm min, Max. 60 °C | UL 94 UL 746 | UL |
| Metal enclosure | Interchangeable | Interchangeable | Thickness: 1.0 mm min | IEC/EN 62368-1 | Tested with appliance |
| Li-ion Battery | Shenzhen JFT Electronics And Technology Co., Ltd | JFT 29125140P | 3.85Vdc, 8000mAh, 30.8Wh | IEC 62133-2 | Report No.: NCT240496 99X11-1 |
| PCB | Guangdong Kingshine Electronic Technology Company Limited | XY-M | V-0, min. 130°C | UL 796 | UL E358874 |
| Internal wire | Interchangeable | Interchangeable | VW-1, 80°C | UL 758 | UL |
| Speaker | Interchangeable | Interchangeable | 1.0W, 7±15%Ω | IEC/EN 62368-1 | Tested with appliance |
| LED panel | Interchangeable | Interchangeable | 11 inch, 1280 x 800 | IEC/EN 62368-1 | Tested with appliance |
| AC ADAPTER | Shenzhen YingQin electronic co., LTD | EE0502000 | Input: 100-240Vac, 50/60Hz, 0.5A; Output: 5Vdc, 2.0A | EN 62368-1 | Report No.: VTC-2019071524 S1; Certification number: VTC-2019071524 |

Supplementary information:

- 1) Provided evidence ensures the agreed level of compliance. See OD-CB2039.

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--------------------|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |

| <h1 style="text-align: center;">TEST REPORT</h1> <p style="text-align: center;">EUROPEAN GROUP DIFFERENCES AND NATIONAL DIFFERENCES (AUDIO/VIDEO, INFORMATION AND COMMUNICATION TECHNOLOGY EQUIPMENT - PART 1: SAFETY REQUIREMENTS)</p> | | | |
|--|---|--|-----|
| Differences according to: EN IEC 62368-1:2020+A11:2020 | | | |
| Attachment Form No: EU_GD_IEC62368_1E | | | |
| Attachment Originator: UL(Demko) | | | |
| Master Attachment: 2021-02-04 | | | |
| Copyright © 2021 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved. | | | |
| | CENELEC COMMON MODIFICATIONS (EN) | | P |
| | <p>Clause numbers in the cells that are shaded light grey are clause references in EN IEC 62368-1:2020+A11:2020. All other clause numbers in that column, except for those in the paragraph below, refers to IEC 62368-1:2018.</p> <p>Clauses, subclauses, notes, tables, figures and annexes which are additional to those in IEC 62368-1:2018 are prefixed "Z".</p> | | P |
| | <p>Add the following annexes:</p> <p>Annex ZA (normative) Normative references to international publications with their corresponding European publications</p> <p>Annex ZB (normative) Special national conditions</p> <p>Annex ZC (informative) A-deviations</p> <p>Annex ZD (informative) IEC and CENELEC code designations for flexible cords</p> | | P |
| 1 | Modification to Clause 3 . | | — |
| 3.3.19 | Sound exposure <i>Replace 3.3.19 of IEC 62368-1 with the following definitions:</i> | | N/A |
| 3.3.19.1 | <p>momentary exposure level, MEL</p> <p>metric for estimating 1 s sound exposure level from the HD 483-1 S2 test signal applied to both channels, based on EN 50332-1:2013, 4.2.</p> <p>Note 1 to entry: MEL is measured as A-weighted levels in dB. Note 2 to entry: See B.3 of EN 50332-3:2017 for additional information.</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 3.3.19.3 | <p>sound exposure, E</p> <p>A-weighted sound pressure (p) squared and integrated over a stated period of time, T</p> <p>Note 1 to entry: The SI unit is Pa² s.</p> $E = \int_0^T p(t)^2 dt$ | | N/A |
| 3.3.19.4 | <p>sound exposure level, SEL</p> <p>logarithmic measure of sound exposure relative to a reference value, E_0, typically the 1 kHz threshold of hearing in humans.</p> <p>Note 1 to entry: SEL is measured as A-weighted levels in dB.</p> $SEL = 10 \lg \left(\frac{E}{E_0} \right) \text{ dB}$ <p>Note 2 to entry: See B.4 of EN 50332-3:2017 for additional information.</p> | | N/A |
| 3.3.19.5 | <p>digital signal level relative to full scale, dBFS</p> <p>levels reported in dBFS are always r.m.s. Full scale level, 0 dBFS, is the level of a dc-free 997-Hz sine wave whose undithered positive peak value is positive digital full scale, leaving the code corresponding to negative digital full scale unused</p> <p>Note 1 to entry: It is invalid to use dBFS for non-r.m.s. levels. Because the definition of full scale is based on a sine wave, the level of signals with a crest factor lower than that of a sine wave may exceed 0 dBFS. In particular, square wave signals may reach +3,01 dBFS.</p> | | N/A |
| 2 | Modification to Clause 10 | | — |
| 10.6 | Safeguards against acoustic energy sources Replace 10.6 of IEC 62368-1 with the following: | | — |
| 10.6.1.1 | <p>Introduction</p> <p>Safeguard requirements for protection against long-term exposure to excessive sound pressure levels from personal music players closely coupled to the ear are specified below. Requirements for earphones and headphones intended for use with personal music players are also covered. A personal music player is a portable equipment intended for use by an ordinary person, that:</p> <p>– is designed to allow the user to listen to audio or</p> | | — |

IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION

| Clause | Requirement - Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

| | | | |
|--|---|--|--|
| | <p>audiovisual content / material; and</p> <ul style="list-style-type: none"> – uses a listening device, such as headphones or earphones that can be worn in or on or around the ears; and – has a player that can be body worn (of a size suitable to be carried in a clothing pocket) and is intended for the user to walk around with while in continuous use (for example, on a street, in a subway, at an airport, etc.). <p>EXAMPLES Portable CD players, MP3 audio players, mobile phones with MP3 type features, PDAs or similar equipment.</p> <p>Personal music players shall comply with the requirements of either 10.6.2 or 10.6.3.</p> <p>NOTE 1 Protection against acoustic energy sources from telecom applications is referenced to ITU-T P.360.</p> <p>NOTE 2 It is the intention of the Committee to allow the alternative methods for now, but to only use the dose measurement method as given in 10.6.5 in future. Therefore, manufacturers are encouraged to implement 10.6.5 as soon as possible.</p> <p>Listening devices sold separately shall comply with the requirements of 10.6.6. These requirements are valid for music or video mode only. The requirements do not apply to:</p> <ul style="list-style-type: none"> – professional equipment; <p>NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.</p> <ul style="list-style-type: none"> – hearing aid equipment and other devices for assistive listening; – the following type of analogue personal music players: <ul style="list-style-type: none"> • long distance radio receiver (for example, a multiband radio receiver or world band radio receiver, an AM radio receiver), and • cassette player/recorder; <p>NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies.</p> <ul style="list-style-type: none"> – a player while connected to an external amplifier that does not allow the user to walk around while in use. <p>For equipment that is clearly designed or intended primarily for use by children, the limits of the relevant toy standards may apply.</p> | | |
|--|---|--|--|

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | The relevant requirements are given in EN 71-1:2011, 4.20 and the related tests methods and measurement distances apply. | | |
| 10.6.1.2 | <p>Non-ionizing radiation from radio frequencies in the range 0 to 300 GHz</p> <p>The amount of non-ionizing radiation is regulated by European Council Recommendation 1999/519/EC of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz). For intentional radiators, ICNIRP guidelines should be taken into account for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). For hand-held and body mounted devices, attention is drawn to EN 50360 and EN 50566.</p> | | — |
| 10.6.2 | <p>Classification of devices without the capacity to estimate sound dose</p> | | — |
| 10.6.2.1 | <p>General</p> <p>This standard is transitioning from short-term based (30 s) requirements to long-term based (40 hour) requirements. These clauses remain in effect only for devices that do not comply with sound dose estimation as stipulated in EN 50332-3.</p> <p>For classifying the acoustic output $L_{Aeq,T}$, measurements are based on the A-weighted equivalent sound pressure level over a 30 s period.</p> <p>For music where the average sound pressure (long term $L_{Aeq,T}$) measured over the duration of the song is lower than the average produced by the programme simulation noise, measurements may be done over the duration of the complete song. In this case, T becomes the duration of the song.</p> <p>NOTE Classical music, acoustic music and broadcast typically has an average sound pressure (long term $L_{Aeq,T}$) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the content and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song does not exceed the required limit.</p> <p>For example, if the player is set with the programme simulation noise to 85 dB, but the average music level of the song is only 65 dB, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dB.</p> | | — |
| 10.6.2.2 | <p>RS1 limits (to be superseded, see 10.6.3.2)</p> <p>RS1 is a class 1 acoustic energy source that does not exceed the following:</p> <ul style="list-style-type: none"> – for equipment provided as a package (player with its listening device), and with a proprietary | | — |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 85 dB when playing the fixed "programme simulation noise" described in EN 50332-1.</p> <ul style="list-style-type: none"> – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 27 mV (analogue interface) or -25 dBFS (digital interface) when playing the fixed "programme simulation noise" described in EN 50332-1. – The RS1 limits will be updated for all devices as per 10.6.3.2. | | |
| 10.6.2.3 | <p>RS2 limits (to be superseded, see 10.6.3.3)</p> <p>RS2 is a class 2 acoustic energy source that does not exceed the following:</p> <ul style="list-style-type: none"> – for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or when the combination of player and listening device is known by other means such as setting or automatic 130 detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 100 dB(A) when playing the fixed "programme simulation noise" as described in EN 50332-1. – for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 150 mV (analogue interface) or -10 dBFS (digital interface) when playing the fixed "programme simulation noise" as described in EN 50332-1. | | — |
| 10.6.2.4 | <p>RS3 limits</p> <p>RS3 is a class 3 acoustic energy source that exceeds RS2 limits.</p> | | — |
| 10.6.3 | Classification of devices (new) | | — |
| 10.6.3.1 | <p>General</p> <p>Previous limits (10.6.2) created abundant false negative and false positive PMP sound level warnings. New limits, compliant with The Commission Decision of 23 June 2009, are given below.</p> | | — |
| 10.6.3.2 | <p>RS1 limits (new)</p> <p>RS1 is a class 1 acoustic energy source that does not exceed the following:</p> | | — |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>– for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the $L_{Aeq,T}$ acoustic output shall be ≤ 80 dB when playing the fixed “programme simulation noise” described in EN 50332-1.</p> <p>– for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output voltage shall be ≤ 15 mV (analogue interface) or -30 dBFS (digital interface) when playing the fixed “programme simulation noise” described in EN 50332-1.</p> | | |
| 10.6.3.3 | <p>RS2 limits (new)</p> <p>RS2 is a class 2 acoustic energy source that does not exceed the following:</p> <p>– for equipment provided as a package (player with its listening device), and with a proprietary connector between the player and its listening device, or where the combination of player and listening device is known by other means such as setting or automatic detection, the weekly sound exposure level, as described in EN 50332-3, shall be ≤ 80 dB when playing the fixed "programme simulation noise" described in EN 50332-1.</p> <p>– for equipment provided with a standardized connector (for example, a 3,5 phone jack) that allows connection to a listening device for general use, the unweighted r.m.s. output level, integrated over one week, as described in EN50332-3, shall be ≤ 15 mV (analogue interface) or -30 dBFS (digital interface) when playing the fixed “programme simulation noise” described in EN 50332-1.</p> | | — |
| 10.6.4 | <p>Requirements for maximum sound exposure</p> | | — |
| 10.6.4.1 | <p>Measurement methods</p> <p>All volume controls shall be turned to maximum during tests.</p> <p>Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable.</p> | | — |
| 10.6.4.2 | <p>Protection of persons</p> <p>Except as given below, protection requirements for parts accessible to ordinary persons, instructed persons and skilled persons are given in 4.3.</p> <p>NOTE 1 Volume control is not considered a safeguard.</p> | | — |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>Between RS2 and an ordinary person, the basic safeguard may be replaced by an instructional safeguard in accordance with Clause F.5, except that the instructional safeguard shall be placed on the equipment, or on the packaging, or in the instruction manual.</p> <p>Alternatively, the instructional safeguard may be given through the equipment display during use.</p> <p>The elements of the instructional safeguard shall be as follows:</p> <ul style="list-style-type: none"> – element 1a: the symbol , IEC 60417-6044 (2011-01) – element 2: “High sound pressure” or equivalent wording – element 3: “Hearing damage risk” or equivalent wording – element 4: “Do not listen at high volume levels for long periods.” or equivalent wording <p>An equipment safeguard shall prevent exposure of an ordinary person to an RS2 source without intentional physical action from the ordinary person and shall automatically return to an output level not exceeding what is specified for an RS1 source when the power is switched off.</p> <p>The equipment shall provide a means to actively inform the user of the increased sound level when the equipment is operated with an output exceeding RS1. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an output exceeding RS1. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time.</p> <p>NOTE 2 Examples of means include visual or audible signals. Action from the user is always needed.</p> <p>NOTE 3 The 20 h listening time is the accumulative listening time, independent of how often and how long the personal music player has been switched off.</p> <p>A skilled person shall not be unintentionally exposed to RS3.</p> | | |
| 10.6.5 | Requirements for dose-based systems | | — |
| 10.6.5.1 | General requirements | | — |
| | <p>Personal music players shall give the warnings as provided below when tested according to EN 50332-3, using the limits from this clause.</p> | | |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>The manufacturer may offer optional settings to allow the users to modify when and how they wish to receive the notifications and warnings to promote a better user experience without defeating the safeguards. This allows the users to be informed in a method that best meets their physical capabilities and device usage needs. If such optional settings are offered, an administrator (for example, parental restrictions, business/educational administrators, etc.) shall be able to lock any optional settings into a specific configuration.</p> <p>The personal music player shall be supplied with easy to understand explanation to the user of the dose management system, the risks involved, and how to use the system safely. The user shall be made aware that other sources may significantly contribute to their sound exposure, for example work, transportation, concerts, clubs, cinema, car races, etc.</p> | | |
| 10.6.5.2 | <p>Dose-based warning and requirements</p> <p>When a dose of 100 % CSD is reached, and at least at every 100 % further increase of CSD, the device shall warn the user and require an acknowledgement. In case the user does not acknowledge, the output level shall automatically decrease to compliance with class RS1.</p> <p>The warning shall at least clearly indicate that listening above 100 % CSD leads to the risk of hearing damage or loss.</p> | | — |
| 10.6.5.3 | <p>Exposure-based requirements</p> <p>With only dose-based requirements, cause and effect could be far separated in time, defying the purpose of educating users about safe listening practice. In addition to dose-based requirements, a PMP shall therefore also put a limit to the short-term sound level a user can listen at.</p> <p>The exposure-based limiter (EL) shall automatically reduce the sound level not to exceed 100 dB(A) or 150 mV integrated over the past 180 s, based on methodology defined in EN 50332-3.</p> <p>The EL settling time (time from starting level reduction to reaching target output) shall be 10 s or faster.</p> <p>Test of EL functionality is conducted according to EN 50332-3, using the limits from this clause. For equipment provided as a package (player with its listening device), the level integrated over 180 s shall be 100 dB or lower. For equipment provided</p> | | — |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>with a standardized connector, the unweighted level integrated over 180 s shall be no more than 150 mV for an analogue interface and no more than -10 dBFS for a digital interface.</p> <p>NOTE In case the source is known not to be music (or test signal), the EL may be disabled.</p> | | |
| 10.6.6 | Requirements for listening devices (headphones, earphones, etc.) | | — |
| 10.6.6.1 | Corded listening devices with analogue input <p>With 94 dB L_{Aeq} acoustic pressure output of the listening device, and with the volume and sound settings in the listening device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output, the input voltage of the listening device when playing the fixed “programme simulation noise” as described in EN 50332-1 shall be ≥ 75 mV.</p> <p>NOTE The values of 94 dB and 75 mV correspond with 85 dB and 27 mV or 100 dB and 150 mV.</p> | | — |
| 10.6.6.2 | Corded listening devices with digital input <p>With any playing device playing the fixed “programme simulation noise” described in EN 50332-1, and with the volume and sound settings in the listening device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output, the $L_{Aeq,\tau}$ acoustic output of the listening device shall be ≤ 100 dB with an input signal of -10 dBFS.</p> | | — |
| 10.6.6.3 | Cordless listening devices <p>In cordless mode,</p> <ul style="list-style-type: none"> – with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and – respecting the cordless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and – with volume and sound settings in the receiving device (for example, built-in volume level control, additional sound features like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the above mentioned programme simulation noise, the $L_{Aeq,\tau}$ acoustic output of the listening device shall be ≤ 100 dB with an input signal of -10 dBFS. | | — |
| 10.6.6.4 | Measurement method | | — |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--------------------|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |

| | | | | | | | |
|----------|--|--------------|-------------------------|-----------------------|-------------|-----------------------|---|
| | <i>Measurements shall be made in accordance with EN 50332-2 as applicable.</i> | | | | | | |
| 3 | Modification to the whole document | | | | | | — |
| | Delete all the “country” notes in the reference document according to the following list: | | | | | | — |
| | 0.2.1 | Note 1 and 2 | 1 | Note 4 and 5 | 3.3.8.1 | Note 2 | |
| | 3.3.8.3 | Note 1 | 4.1.15 | Note | 4.7.3 | Note 1 and 2 | |
| | 5.2.2.2 | Note | 5.4.2.3.2.2 Table 12 | Note c | 5.4.2.3.2.4 | Note 1 and 3 | |
| | 5.4.2.3.2.4 Table 13 | Note 2 | 5.4.2.5 | Note 2 | 5.4.5.1 | Note | |
| | 5.4.10.2.1 | Note | 5.4.10.2.2 | Note | 5.4.10.2.3 | Note | |
| | 5.5.2.1 | Note | 5.5.6 | Note | 5.6.4.2.1 | Note 2 and 3 and 4 | |
| | 5.6.8 | Note 2 | 5.7.6 | Note | 5.7.7.1 | Note 1 and Note 2 | |
| | 8.5.4.2.3 | Note | 10.2.1 Table 39 | Note 3 and 4 and 5 | 10.5.3 | Note 2 | |
| | 10.6.4 | Note 3 | F.3.3.6 | Note 3 | Y.4.1 | Note | |
| | Y.4.5 | Note | | | | | |
| 4 | Modification to Clause 1 | | | | | | — |
| 1 | Add the following note: <i>NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2011/65/EU.</i> | | | | | | P |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 5 | Modification to 4.Z1 | | — |
| 4.Z1 | <p>Add the following new subclause after 4.9:</p> <p>To protect against excessive current, short-circuits and earth faults in circuits connected to an a.c. mains, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c):</p> <p>a) except as detailed in b) and c), protective devices necessary to comply with the requirements of B.3.1 and B.4 shall be included as parts of the equipment;</p> <p>b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;</p> <p>c) it is permitted for pluggable equipment type B or permanently connected equipment, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions.</p> <p>If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for pluggable equipment type A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.</p> | | N/A |
| 6 | Modification to 5.4.2.3.2.4 | | — |
| 5.4.2.3.2.4 | <p>Add the following to the end of this subclause:</p> <p>The requirement for interconnection with external circuit is in addition given in EN 50491-3:2009.</p> | | N/A |
| 7 | Modification to 10.2.1 | | — |
| 10.2.1 | <p>Add the following to ^{c)} and ^{d)} in table 39:</p> <p>For additional requirements, see 10.5.1.</p> | | N/A |

| IEC 62368-1_ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 8 | Modification to 10.5.1 | | — |
| 10.5.1 | <p>Add the following after the first paragraph:</p> <p>For RS 1 compliance is checked by measurement under the following conditions:</p> <p>In addition to the normal operating conditions, all controls adjustable from the outside by hand, by any object such as a tool or a coin, and those internal adjustments or pre-sets which are not locked in a reliable manner, are adjusted so as to give maximum radiation whilst maintaining an intelligible picture for 1 h, at the end of which the measurement is made.</p> <p>NOTE Z1 Soldered joints and paint lockings are examples of adequate locking.</p> <p>The dose-rate is determined by means of a radiation monitor with an effective area of 10 cm², at any point 10 cm from the outer surface of the apparatus.</p> <p>Moreover, the measurement shall be made under fault conditions causing an increase of the high voltage, provided an intelligible picture is maintained for 1 h, at the end of which the measurement is made.</p> <p>For RS1, the dose-rate shall not exceed 1 μSv/h taking account of the background level.</p> <p>NOTE Z2 These values appear in Directive 96/29/Euratom of 13 May 1996.</p> | | N/A |
| 9 | Modification to G.7.1 | | — |
| G.7.1 | <p>Add the following note:</p> <p>NOTE Z1 The harmonized code designations corresponding to the IEC cord types are given in Annex ZD.</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 10 | Modification to Bibliography | | — |
| | <p>Add the following notes for the standards indicated:</p> <p>IEC 60130-9 NOTE Harmonized as EN 60130-9. IEC 60269-2 NOTE Harmonized as HD 60269-2. IEC 60309-1 NOTE Harmonized as EN 60309-1. IEC 60364 NOTE some parts harmonized in HD 384/HD 60364 series. IEC 60601-2-4 NOTE Harmonized as EN 60601-2-4. IEC 60664-5 NOTE Harmonized as EN 60664-5. IEC 61032:1997 NOTE Harmonized as EN 61032:1998 (not modified). IEC 61508-1 NOTE Harmonized as EN 61508-1. IEC 61558-2-1 NOTE Harmonized as EN 61558-2-1. IEC 61558-2-4 NOTE Harmonized as EN 61558-2-4. IEC 61558-2-6 NOTE Harmonized as EN 61558-2-6. IEC 61643-1 NOTE Harmonized as EN 61643-1. IEC 61643-21 NOTE Harmonized as EN 61643-21. IEC 61643-311 NOTE Harmonized as EN 61643-311. IEC 61643-321 NOTE Harmonized as EN 61643-321. IEC 61643-331 NOTE Harmonized as EN 61643-331.</p> | | N/A |
| 11 | ADDITION OF ANNEXES | | — |
| ZB | ANNEX ZB, SPECIAL NATIONAL CONDITIONS (EN) | | — |
| 4.1.15 | <p>Denmark, Finland, Norway and Sweden</p> <p>To the end of the subclause the following is added: Class I pluggable equipment type A intended for connection to other equipment or a network shall, if safety relies on connection to reliable earthing or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment shall be connected to an earthed mains socket-outlet.</p> <p>The marking text in the applicable countries shall be as follows:</p> <p>In Denmark: "Apparatets stikprop skal tilsluttes en stikkontakt med jord som giver forbindelse til stikproppens jord." In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan" In Norway: "Apparatet må tilkoples jordet stikkontakt" In Sweden: "Apparaten skall anslutas till jordat uttag"</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 4.7.3 | <p>United Kingdom</p> <p>To the end of the subclause the following is added:</p> <p>The torque test is performed using a socket-outlet complying with BS 1363, and the plug part shall be assessed to the relevant clauses of BS 1363. Also see Annex G.4.2 of this annex</p> | | N/A |
| 5.2.2.2 | <p>Denmark</p> <p>After the 2nd paragraph add the following:</p> <p>A warning (marking safeguard) for high touch current is required if the touch current exceeds the limits of 3,5 mA a.c. or 10 mA d.c.</p> | | N/A |
| 5.4.11.1 and Annex G | <p>Finland and Sweden</p> <p>To the end of the subclause the following is added:</p> <p>For separation of the telecommunication network from earth the following is applicable:</p> <p>If this insulation is solid, including insulation forming part of a component, it shall at least consist of either</p> <ul style="list-style-type: none"> two layers of thin sheet material, each of which shall pass the electric strength test below, or one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below. <p>If this insulation forms part of a semiconductor component (e.g. an optocoupler), there is no distance through insulation requirement for the insulation consisting of an insulating compound completely filling the casing, so that clearances and creepage distances do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition</p> <ul style="list-style-type: none"> passes the tests and inspection criteria of 5.4.8 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 5.4.9 shall be performed using 1,5 kV), <p>and</p> <ul style="list-style-type: none"> is subject to routine testing for electric strength during manufacturing, using a test voltage of 1,5 kV. <p>It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005,</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>subclass Y2.</p> <p>A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the following conditions:</p> <ul style="list-style-type: none"> the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in 5.4.11; the additional testing shall be performed on all the test specimens as described in EN 60384-14; <p>the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.</p> | | |
| 5.5.2.1 | <p>Norway</p> <p>After the 3rd paragraph the following is added:</p> <p>Due to the IT power system used, capacitors are required to be rated for the applicable line-to-line voltage (230 V).</p> | | N/A |
| 5.5.6 | <p>Finland, Norway and Sweden</p> <p>To the end of the subclause the following is added:</p> <p>Resistors used as basic safeguard or bridging basic insulation in class I pluggable equipment type A shall comply with G.10.1 and the test of G.10.2.</p> | | N/A |
| 5.6.1 | <p>Denmark</p> <p>Add to the end of the subclause Due to many existing installations where the socket-outlets can be protected with fuses with higher rating than the rating of the socket-outlets the protection for pluggable equipment type A shall be an integral part of the equipment. <i>Justification:</i> In Denmark an existing 13 A socket outlet can be protected by a 20 A fuse.</p> | | N/A |
| 5.6.4.2.1 | <p>Ireland and United Kingdom</p> <p>After the indent for pluggable equipment type A, the following is added: – the protective current rating is taken to be 13 A, this being the largest rating of fuse used in the mains plug.</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| 5.6.4.2.1 | <p>France</p> <p>After the indent for pluggable equipment type A, the following is added: – in certain cases, the protective current rating of the circuit supplied from the mains is taken as 20 A instead of 16 A.</p> | | N/A |
| 5.6.5.1 | <p>To the second paragraph the following is added:</p> <p>The range of conductor sizes of flexible cords to be accepted by terminals for equipment with a rated current over 10 A and up to and including 13 A is: 1,25 mm² to 1,5 mm² in cross-sectional area.</p> | | N/A |
| 5.6.8 | <p>Norway</p> <p>To the end of the subclause the following is added: Equipment connected with an earthed mains plug is classified as class I equipment. See the Norway marking requirement in 4.1.15. The symbol IEC 60417-6092, as specified in F.3.6.2, is accepted.</p> | | N/A |
| 5.7.6 | <p>Denmark</p> <p>To the end of the subclause the following is added: The installation instruction shall be affixed to the equipment if the protective conductor current exceeds the limits of 3,5 mA a.c. or 10 mA d.c.</p> | | N/A |
| 5.7.6.2 | <p>Denmark</p> <p>To the end of the subclause the following is added: The warning (marking safeguard) for high touch current is required if the touch current or the protective current exceed the limits of 3,5 mA .</p> | | N/A |
| 5.7.7.1 | <p>Norway and Sweden</p> <p>To the end of the subclause the following is added: The screen of the television distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation needs to be isolated from the screen of a cable distribution system.</p> <p>It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by a retailer, for example.</p> <p>The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in:</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| | <p>“Apparatus connected to the protective earthing of the building installation through the mains connection or through other apparatus with a connection to protective earthing – and to a television distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a television distribution system therefore has to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)”</p> <p>NOTE In Norway, due to regulation for CATV-installations, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min.</p> <p>Translation to Norwegian (the Swedish text will also be accepted in Norway):</p> <p>“Apparater som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et koaksialbasert kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av apparater til kabel-TV nett installeres en galvanisk isolator mellom apparatet og kabel-TV nettet.”</p> <p>Translation to Swedish: ”Apparater som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av apparaten till kabel-TV nät galvanisk isolator finnas mellan apparaten och kabel-TV nätet.”</p> | | |
| 8.5.4.2.3 | <p>United Kingdom</p> <p>Add the following after the 2nd dash bullet in 3rd paragraph:</p> <p>An emergency stop system complying with the requirements of IEC 60204-1 and ISO 13850 is required where there is a risk of personal injury.</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| B.3.1 and B.4 | <p>Ireland and United Kingdom</p> <p>The following is applicable:</p> <p>To protect against excessive currents and short-circuits in the primary circuit of direct plug-in equipment, tests according to Annexes B.3.1 and B.4 shall be conducted using an external miniature circuit breaker complying with EN 60898-1, Type B, rated 32A. If the equipment does not pass these tests, suitable protective devices shall be included as an integral part of the direct plug-in equipment, until the requirements of Annexes B.3.1 and B.4 are met</p> | | N/A |
| G.4.2 | <p>Denmark</p> <p>To the end of the subclause the following is added:</p> <p>Supply cords of single phase appliances having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1:2011.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.</p> <p>If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a polyphase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2.</p> <p>Mains socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance DS 60884-2-D1:2011 standard sheet DKA 1-4a.</p> <p>Other current rating socket outlets shall be in compliance with Standard Sheet DKA 1-3a or DKA 1-1c.</p> <p>Mains socket-outlets with earth shall be in compliance with DS 60884-2-D1:2011 Standard Sheet DK 1-3a, DK 1-1c, DK1-1d, DK 1-5a or DK 1-7a</p> <p><i>Justification:</i> Heavy Current Regulations, Section 6c</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|---|---------------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| G.4.2 | <p>United Kingdom</p> <p>To the end of the subclause the following is added:</p> <p>The plug part of direct plug-in equipment shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16, and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.</p> | Class III appliance | N/A |
| G.7.1 | <p>United Kingdom</p> <p>To the first paragraph the following is added:</p> <p>Equipment which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord shall be fitted with a 'standard plug' in accordance with the Plugs and Sockets etc. (Safety) Regulations 1994, Statutory Instrument 1994 No. 1768, unless exempted by those regulations.</p> <p>NOTE "Standard plug" is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.</p> | | N/A |
| G.7.1 | <p>Ireland</p> <p>To the first paragraph the following is added:</p> <p>Apparatus which is fitted with a flexible cable or cord shall be provided with a plug in accordance with Statutory Instrument 525: 1997, "13 A Plugs and Conversion Adapters for Domestic Use Regulations: 1997. S.I. 525 provides for the recognition of a standard of another Member State which is equivalent to the relevant Irish Standard</p> | | N/A |
| G.7.2 | <p>Ireland and United Kingdom</p> <p>To the first paragraph the following is added:</p> <p>A power supply cord with a conductor of 1,25 mm² is allowed for equipment which is rated over 10 A and up to and including 13 A.</p> | | N/A |

| IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION | | | |
|--|--|-----------------|---------|
| Clause | Requirement - Test | Result - Remark | Verdict |
| ZC | ANNEX ZC, NATIONAL DEVIATIONS (EN) | | — |
| 10.5.2 | <p>Germany</p> <p>The following requirement applies:</p> <p>For the operation of any cathode ray tube intended for the display of visual images operating at an acceleration voltage exceeding 40 kV, authorization is required, or application of type approval (Bauartzulassung) and marking.</p> <p><i>Justification:</i> German ministerial decree against ionizing radiation (Röntgenverordnung), in force since 2002-07-01, implementing the European Directive 96/29/EURATOM.</p> <p>NOTE Contact address: Physikalisch-Technische Bundesanstalt, Bundesallee 100, D-38116 Braunschweig, Tel.: Int+49-531-592-6320, Internet: http://www.ptb.de</p> | | N/A |

IEC 62368-1 ATTACHMENT 1: NATIONAL DEVIATION

| Clause | Requirement - Test | Result - Remark | Verdict |
|--------|--------------------|-----------------|---------|
|--------|--------------------|-----------------|---------|

| ZD | IEC and CENELEC CODE DESIGNATIONS FOR FLEXIBLE CORDS (EN) | | — |
|----|---|-------------------|--------------------------|
| | Type of flexible cord | Code designations | |
| | | IEC | CENELEC |
| | PVC insulated cords | | |
| | Flat twin tinsel cord | 60227 IEC 41 | H03VH-Y |
| | Light polyvinyl chloride sheathed flexible cord | 60227 IEC 52 | H03VV-F H03VVH2-F |
| | Ordinary polyvinyl chloride sheathed flexible cord | 60227 IEC 53 | H05VV-F H05VVH2-F |
| | Rubber insulated cords | | |
| | Braided cord | 60245 IEC 51 | H03RT-F |
| | Ordinary tough rubber sheathed flexible cord | 60245 IEC 53 | H05RR-F |
| | Ordinary polychloroprene sheathed flexible cord | 60245 IEC 57 | H05RN-F |
| | Heavy polychloroprene sheathed flexible cord | 60245 IEC 66 | H07RN-F |
| | Cords having high flexibility | | |
| | Rubber insulated and sheathed cord | 60245 IEC 86 | H03RR-H |
| | Rubber insulated, crosslinked PVC sheathed cord | 60245 IEC 87 | H03RV4-H |
| | Crosslinked PVC insulated and sheathed cord | 60245 IEC 88 | H03V4V4-H |
| | Cords insulated and sheathed with halogen-free thermoplastic compounds | | |
| | Light halogen-free thermoplastic insulated and sheathed flexible cords | | H03Z1Z1-F H03Z1Z1H2-F |
| | Ordinary halogen-free thermoplastic insulated and sheathed flexible cords | | H05Z1Z1-F H05Z1Z1H2-F |

PHOTO DOCUMENTATION_ATTACHMENT 2




Photo 1: External view



Photo 2: External view



Photo 3: External view




Photo 4: External view



Photo 5: Port view



Photo 6: Port view




Photo 7: Internal view




Photo 8: Internal view




Photo 9: Internal view




Photo 10: Battery view



Photo 11: Internal view




Photo 12: Internal view




Photo 13: Internal view




Photo 14: Internal view




Photo 15: PCB view




Photo 16: PCB view




Photo 17: PCB view




Photo 18: PCB view

*****End of the report*****