HEALTH TEST REPORT

For

Shenzhen PXN Electronics Technology Co., Ltd

Game Controller

Test Model: P5

Additional Model No.: Please Refer to Page 5

Prepared for	:	Shenzhen PXN Electronics Technology Co., Ltd
Address	:	1701-1706(01), Building 8, Zhongxi Xiangbinshan Garden, Fenghuanggang Community, Xixiang Street, Baoan District, Shenzhen
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	October 31, 2024
Number of tested samples	:	2
Sample No.	:	A241031018-1, A241031018-2
Serial number	:	Prototype
Date of Test	:	October 31, 2024 ~ November 18, 2024
Date of Report	:	November 19, 2024

CE

HEALTH TEST REPORT EN 62479:2010 & EN 50663:2017	
Report Reference No.	**: LCSA10114051ED**
Date of Issue.....	: November 19, 2024
Testing Laboratory Name.....	**: Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address.....	: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Testing Location/ Procedure....	: Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's Name.....	**: Shenzhen PXN Electronics Technology Co., Ltd**
Address.....	: 1701-1706(01), Building 8, Zhongxi Xiangbinshan Garden, Fenghuanggang Community, Xixiang Street, Baoan District, Shenzhen
Test Specification	
Standard.....	: EN 62479:2010 EN 50663:2017
Test Report Form No.	: TRF-4-E-155 A/0
TRF Originator.....	: Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF.....	: Dated 2011-03

Test Item Description.....	**: Game Controller**
Trade Mark.....	: PXN
Test Model.....	: P5
Ratings	: Input: 5V⎓300mA DC 3.7V by Rechargeable Li-ion Battery, 1000mAh
Result	**: Positive**

Compiled by:	Supervised by:	Approved by:
Li Huan/ Administrator	Cary Luo/ Technique principal	Gavin Liang/ Manager

HEALTH --TEST REPORT

Test Report No. : LCSA10114051ED	November 19, 2024 Date of issue

Test Model	: P5
EUT.....	: Game Controller
Applicant.....	**: Shenzhen PXN Electronics Technology Co., Ltd**
Address.....	: 1701-1706(01), Building 8, Zhongxi Xiangbinshan Garden, Fenghuanggang Community, Xixiang Street, Baoan District, Shenzhen
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: Shenzhen PXN Electronics Technology Co., Ltd**
Address.....	: 1701-1706(01), Building 8, Zhongxi Xiangbinshan Garden, Fenghuanggang Community, Xixiang Street, Baoan District, Shenzhen
Telephone.....	: /
Fax.....	: /
Factory.....	**: Shenzhen PXN Electronics Technology Co., Ltd**
Address.....	: 1701-1706(01), Building 8, Zhongxi Xiangbinshan Garden, Fenghuanggang Community, Xixiang Street, Baoan District, Shenzhen
Telephone.....	: /
Fax.....	: /

Test Result	Positive

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Report Version	Issue Date	Revision Content	Revised By
000	November 19, 2024	Initial Issue	---

1. GENERAL INFORMATION

1.1. Product Description for Equipment Under Test (EUT)

EUT	:	Game Controller
Test Model	:	P5
Additional Model No.	:	P5S, P5X, P5L, R5PRO, P5Lite, P5 Gen2, P5NL, P5Pro, P5Ultra, R5, P5Plus, P5 8K
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Ratings	:	Input: 5V⎓300mA DC 3.7V by Rechargeable Li-ion Battery, 1000mAh
Hardware Version	:	VER:A4
Software Version	:	V1.20
Bluetooth	:	
Frequency Range	:	2402MHz~2480MHz
Channel Number	:	79 channels for Bluetooth V5.0 (BDR/EDR) 40 channels for Bluetooth V5.0 (BT LE)
Channel Spacing	:	1MHz for Bluetooth V5.0 (BDR/EDR) 2MHz for Bluetooth V5.0 (BT LE)
Modulation Type	:	GFSK, π/4-DQPSK, 8-DPSK for Bluetooth V5.0 (BDR/EDR) GFSK for Bluetooth V5.0 (BT LE)
Bluetooth Version	:	V5.0
Antenna Description	:	PCB Antenna, -2.30dBi(max.)

1.2. Objective

According to its specifications, the EUT must comply with the requirements of the following standards:
EN 62479:2010-Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)
EN 50663:2017-Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz).

1.3. Test Methodology

All measurements contained in this report were conducted with EN 62479:2010 and EN 50663:2017.

1.4. Facilities

All measurement facilities used to collect the measurement data are located at Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China .
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 32.

1.5. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050200 UU	---	CE

Note: The adapter is supplied by lab and only use tested.

1.6. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 0.8m, unshielded

1.7. Equipment

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.
All receiving equipment conforms to CISPR Publication 16-1, “Radio Interference Measuring Apparatus and Measurement Methods.”

1.8. Laboratory Accreditations And Listings

Site Description		
EMC Lab.	:	NVLAP Accreditation Code is 600167-0. FCC Designation Number is CN5024. CAB identifier is CN0071. CNAS Registration Number is L4595.
Name of Firm	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Site Location	:	Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao’an District, Shenzhen, Guangdong, China

1.9. Measurement Uncertainty

Test Item		Uncertainty
Radio Frequency	:	0.9×10^{-4}
Total RF Power, Conducted	:	1.0 dB
RF Power Density, Conducted	:	1.8 dB
Spurious Emissions, Conducted	:	1.8 dB
All Emissions, Radiated	:	3.1 dB
Temperature	:	0.5°C
Humidity	:	1 %
DC And Low Frequency Voltages	:	1 %

2. HUMAN EXPOSURE TO THE ELECTROMAGNETIC FIELDS

2.1 Test Methodology

2.1.1.General description of applied standards

According to its specifications, the EUT must comply with the requirements of the following standards:
EN 62479-Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)
EN 50663-Generic standard for assessment of low power electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (10 MHz - 300 GHz).

2.1.2.Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

2.2 Test limit

If the average power emitted by apparatus operating in the frequency range 10 MHz – 300GHz is less than or equal to 20 mW and the transmitting peak power is less than 20 mW then the apparatus is deemed to comply with the basic restrictions without testing.

2.3 Test Results

Since Max. output power for Bluetooth is 1.50mW (1.77dBm According to radio test report LCSA10114051EB, LCSA10114051EC) less than 20mW specified in EN 62479 and EN 50663. This unit will not generate the harmful EM emission above the reference level as specified in EC Council Recommendation (1999/519/EC).

The unit complies with the EN 62479 and EN 50663 for RF exposure requirement.

No non-compliance noted.

----------THE END OF TEST REPORT----------