



Report No.: TW2409129E

Applicant: Eastern Times Technology Co., Ltd

Product: 3-MODES 98 KEY CASKET HOT-SWAPPABLE RGB MECHANICAL

Trademark: REDRAGON

Model No.: K686WB-RGB-PRO, K686AK-RGB-PRO, ET-7199, K688GB-RGB-PRO

Test Standards: EN 55032:2015+A11:2020+A1:2020
EN IEC 61000-3-2:2019 +A1:2021
EN 55035:2017+A11:2020
EN 61000-3-3:2013+A2:2021+AC:2022-01

Test Result: The EMC testing has been performed on the submitted samples and found in compliance with council EMC Directive 2014/30/EU.

Approved By

A handwritten signature in black ink that reads 'Terry Tang'.

Terry Tang

Manager

Dated: September 14, 2024

**Results appearing herein relate only to the sample tested
The technical reports is issued errors and omissions exempt and is subject to
withdrawal at**

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West,
Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

TEST REPORT



Special Statement:

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) —Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

CAB identifier: CN0033

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



TABLE OF CONTENT

Test Report Conclusion	
Special Statement	
Content	
1.0 General Details	5
1.1 Test Lab Details	5
1.2 Applicant Details	5
1.3 Description of EUT	5
1.4 Submitted Sample	5
1.5 Test Duration	6
1.6 Additional Information of EUT	6
1.7 Test Engineer & Verify Engineer	6
2.0 List of Measurement Equipment	7
2.1 Conducted Emission Test	7
2.2 Radiated Disturbance Test	7
2.3 Harmonic & Flicker Test	7
2.4 ESD Test	7
2.5 RF Field Strength Susceptibility	7
2.6 Electrical Fast Transient/Burst (EFT/B) Immunity Test	8
2.7 Surge Test	8
2.8 Conducted Immunity Test	8
2.9 Power-Frequency Magnetic Field	8
2.10 Voltage Dips/Interruption Immunity Test	9
3.0 Technical Details	10
3.1 Investigations Requested	10
3.2 Test Standards	10
3.3 Performance Criteria	10
3.4 Test Standards and Results Summary Tables	11
4.0 Electromagnetic Interference Test Results	12

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer, Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



4.1	Power line Conducted Emission Test.....	12
4.2	Telecommunication Ports Conducted Emission Test.....	15
4.3	Radiated Disturbance Test.....	18
4.4	Harmonic Current Emission Test.....	23
4.5	Voltage Fluctuations & Flicker Test.....	25
5.0	Immunity Test.....	26
5.1	Electrostatic Discharge.....	26
5.2	RF Field transients / Burst Immunity Test.....	28
5.3	Electrical Fast Transient/Burst (EFT/B) immunity test.....	30
5.4	Surge Test.....	32
5.5	Conducted Immunity Test.....	34
5.6	Power-Frequency Magnetic Field.....	36
5.7	Voltage Dips / Interruptions Immunity Test.....	38
6.0	Product Labeling.....	40
6.1	CE Mark label specification.....	40
	Appendix.....	41

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



1.0 General Details

1.1 Test Lab Details

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel: +86 755 83448688 Fax: +86 755 83442996

Test Location

All tests were performed at:

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel: +86 755 83448688 Fax: +86 755 83442996

1.2 Applicant Details

Applicant: Eastern Times Technology Co., Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City, Guangdong, China.

Manufacturer: Eastern Times Technology Co., Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City, Guangdong, China.

1.3 Description of EUT

Product: 3-MODES 98 KEY CASSET HOT-SWAPPABLE RGB MECHANICAL

Trademark: REDRAGON

Model Number: K686WB-RGB-PRO

Adding Trademark: N/A

Adding Model Number: K686AK-RGB-PRO, ET-7199, K688GB-RGB-PRO

Rating: Input: DC5V, 500mA or DC3.7V, 120mA

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



2.0 List of Measurement Equipment

2.1 Conducted Emission Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
EMI Test Receiver	ESCS 30	834115/006	RS	2024.07.12	1Year
LISN	NNB42	00012	SCHAFFNER	2024.07.12	1Year

2.2 Radiated Disturbance Test

Name	Model No	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
EMI Test Receiver	ESPI 3	100379	RS	2024.07.12	1Year
Spectrum Analyzer	E4407B	MY50441392	HP/Agilent	2024.07.12	1Year
Amplifier	BBV9743	#218	HP/Agilent	2024.07.12	1Year
Bilog Antenna	VULB9163	9163/340	Schwarebeck	2022.07.18	3Year
Horn Antenna	BBHA 9120D	9120D-631	RS	2022.07.18	3Year
Amplifier	8449B	3008A00160	HP/Agilent	2024.07.12	1Year

2.3 Harmonic & Flicker Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Harmonics Flicker Test System	PACS-1	72305	CI	2024.07.12	1Year
5K VA AC Power Source	5001iX	56060	CI	2024.07.12	N/A

2.4 ESD Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
------	-----------	------------	--------------	------------------	-------------------

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



ESD Simulator	DITO	0404-24	EM TEST	2024.07.12	1Year
---------------	------	---------	---------	------------	-------

2.5 RF field Strength Susceptibility

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Signal Generator	SMT03	100059	RS	2024.07.12	1Year
Power Meter	NRVS	---	RS	2024.07.12	1Year
Voltage Probe	URV5-Z2	100012	RS	2024.07.12	1Year
Voltage Probe	URV5-Z2	100013	RS	2024.07.12	1Year
Power Amplifier	150W1000	300999	AR	2024.07.12	1Year
Power Amplifier	25S1G4AM1	305993	AR	2024.07.12	1Year
Field Probe	CBL6111C	2576	Holaday	2024.07.12	1Year
Bilog Antenna	MCDC	---	Chase	2024.07.12	1Year

2.6 Electrical Fast Transient/Burst (EFT/B) Immunity test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
EFT Generator	UCS 500 M4	0304-42	EM TEST	2024.07.12	1Year
Power Source	MV2616	0104-14	EM TEST	2024.07.12	1Year

2.7 Surge Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Ultra Compact Simulator	UCS 500 M4	0304-42	EM TEST	2024.07.12	1Year
Power Source	MV2616	0104-14	EM TEST	2024.07.12	1Year

2.8 Conducted Immunity Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Continuous Wave Simulator	CWS 500C	0407-05	EM TEST	2024.07.12	1 Year

2.9 Power-frequency Magnetic Field

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Continuous Wave	UCS 500 M4	0304-42	EM TEST	2024.07.12	1 Year

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Simulator					
Power Source					
Network	MV 2616	0104-14	EM TEST	2024.07.12	1 Year
Current Transformer	MC2630	--	EM TEST	2024.07.12	1 Year
Magnetic Coil	MS100	0304-42	EM TEST	2024.07.12	1 Year

2.10 Voltage Dips/Interruption Immunity Test

Name	Model No.	Serial No.	Manufacturer	Calibration Date	Calibration Cycle
Ultra Compact Simulator	UCS 500 M4	0304-42	EM TEST	2024.07.12	1Year
Power Source	MV2616	0104-14	EM TEST	2024.07.12	1Year

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



3.0 Technical Details

3.1 Investigations Requested

Perform Electromagnetic Interference [EMI] & Electromagnetic Susceptibility [EMS] tests for CE Marking

3.2 Test Standards

Test Standards		
EN 55032:2015+A11:2020+A1:2020	Electromagnetic compatibility of multimedia equipment - Emission Requirements	
EN IEC 61000-3-2:2019+ A1:2021	Electromagnetic compatibility(EMC)- Part 3-2:Limits-Limits for harmonic current emissions(equipment input current \leq 16A per phase)	
EN 61000-3-3:2013 +A2:2021+AC:2022-01	Electromagnetic compatibility (EMC)- Part 3-3: Limits-Limitation of voltage changes, Voltage fluctuations and flicker in public low-voltage supply systems. For equipment with rated current \leq 16A per phase and not subject to conditional connection	
EN 55035:2017+A11:2020	Electromagnetic compatibility of multimedia equipment - Immunity requirements	
	EN 61000-4-2:2009	Electrostatic discharge
	EN IEC 61000-4-3:2020	RF electromagnetic field disturbances
	EN 61000-4-4:2012	Electrical Fast transients
	EN 61000-4-5:2014	Surge
	EN 61000-4-6:2014	Conducted susceptibility
	EN 61000-4-8:2010	Power-frequency Magnetic Field
	EN IEC 61000-4-11: 2020	Dips/Voltage Interruption Variation

3.3 Performance Criteria

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

3.4 Test standards and Results Summary Tables

Test Condition	Test Requirement	Test Method	Test Result
EMISSION Results Summary			
Conducted Emission on AC Mains, 150kHz to 30MHz	EN 55032:2015 +A11:2020+A1:2020	EN 55032:2015 +A11:2020+A1:2020	Pass
Conducted Emission on at telecommunication ports, 150kHz to 30MHz	EN 55032:2015 +A11:2020+A1:2020	EN 55032:2015 +A11:2020+A1:2020	N/A
Radiated Emissions, 30MHz to 6GHz	EN 55032:2015 +A11:2020+A1:2020	EN 55032:2015 +A11:2020+A1:2020	Pass
Harmonic Emissions on AC supply	EN IEC 61000-3-2:2019 +A1:2021	EN IEC 61000-3-2:2019 +A1:2021	N/A
Voltage fluctuations on AC supply	EN 61000-3-3:2013 +A2:2021+AC:2022-01	EN 61000-3-3:2013 +A2:2021+AC:2022-01	N/A
IMMUNITY Results Summary			
Electrostatic Discharge	EN 55035:2017+A11:2020	EN 61000-4-2: 2009	Pass
Continuous RF electromagnetic field disturbances	EN 55035:2017+A11:2020	EN IEC 61000-4-3:2020	Pass
Continuous induced RF disturbances	EN 55035:2017+A11:2020	EN 61000-4-6:2014	Pass
Power frequency magnetic field	EN 55035:2017+A11:2020	EN 61000-4-8: 2010	N/A
Electrical fast transients/burst (EFT/B)	EN 55035:2017+A11:2020	EN 61000-4-4: 2012	Pass
Surges	EN 55035:2017+A11:2020	EN 61000-4-5: 2014	Pass
Voltage dips and interruptions	EN 55035:2017+A11:2020	EN IEC 61000-4-11: 2020	Pass

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Broadband impulsive conducted disturbances	EN 55035:2017+A11:2020	EN 61000-4-6:2014	N/A
--	------------------------	-------------------	-----

Note: N/A-Not applicable

4.0 Electromagnetic Interference Test results

4.1 Power line Conducted Emission Test


4.1.1 Schematics of the test



4.1.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



4.1.3 Power line conducted Emission Limit

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer, Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Frequency(MHz)	Limits dB(μV)			
	Class A Equipment		Class B Equipment	
	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level
0.15 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*
0.50 ~ 5.00	73.0	60.0	56.0	46.0
5.00 ~ 30.00	73.0	60.0	60.0	50.0

Notes: 1. *decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies

4.1.4 Test Results

Limits for Conducted Emission test, please refer to limit line (Quasi-peak) and Average in the following diagram labelled as (QP)&AV

Remark: Calculated measurement uncertainty=3.6dB

A: Disturbance Voltage Limits at mains on Live terminals (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Wired Operation Mode

Power: AC230V/50Hz

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1578	42.39	9.78	52.17	65.58	-13.41	QP	P
2	0.1578	23.87	9.78	33.65	55.58	-21.93	AVG	P
3	0.2202	33.70	9.75	43.45	62.81	-19.36	QP	P
4	0.2202	18.61	9.75	28.36	52.81	-24.45	AVG	P
5	0.4269	23.69	9.77	33.46	57.31	-23.85	QP	P
6	0.4269	13.25	9.77	23.02	47.31	-24.29	AVG	P
7	4.5717	16.57	9.91	26.48	56.00	-29.52	QP	P
8	4.5717	8.25	9.91	18.16	46.00	-27.84	AVG	P

B: Disturbance Voltage Limits at mains on Neutral terminals (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Wired Operation Mode

Power: AC230V/50Hz

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1773	34.82	9.77	44.59	64.61	-20.02	QP	P
2	0.1773	14.33	9.77	24.10	54.61	-30.51	AVG	P
3	0.2943	31.31	9.76	41.07	60.40	-19.33	QP	P
4	0.2943	28.25	9.76	38.01	50.40	-12.39	AVG	P
5	4.1388	17.84	9.89	27.73	56.00	-28.27	QP	P
6	4.1388	6.96	9.89	16.85	46.00	-29.15	AVG	P
7	17.1999	17.89	10.51	28.40	60.00	-31.60	QP	P
8	17.1999	12.77	10.51	23.28	50.00	-26.72	AVG	P

C: Disturbance Voltage Limits at mains on Live terminals (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Charging

Power: AC230V/50Hz

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2943	29.02	9.76	38.78	60.40	-21.62	QP	P
2	0.2943	27.55	9.76	37.31	50.40	-13.09	AVG	P
3	0.6999	22.06	9.78	31.84	56.00	-24.16	QP	P
4	0.6999	13.12	9.78	22.90	46.00	-23.10	AVG	P
5	2.7864	19.76	9.83	29.59	56.00	-26.41	QP	P
6	2.7864	9.81	9.83	19.64	46.00	-26.36	AVG	P
7	25.2300	26.73	11.00	37.73	60.00	-22.27	QP	P
8	25.2300	20.56	11.00	31.56	50.00	-18.44	AVG	P

D: Disturbance Voltage Limits at mains on Neutral terminals (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa


EUT set Condition: Charging

Power: AC230V/50Hz

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual




The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1734	29.32	9.77	39.09	64.80	-25.71	QP	P
2	0.1734	11.22	9.77	20.99	54.80	-33.81	AVG	P
3	0.2163	24.01	9.75	33.76	62.96	-29.20	QP	P
4	0.2163	8.89	9.75	18.64	52.96	-34.32	AVG	P
5	1.8231	15.57	9.80	25.37	56.00	-30.63	QP	P
6	1.8231	8.61	9.80	18.41	46.00	-27.59	AVG	P
7	11.9154	21.69	10.24	31.93	60.00	-28.07	QP	P
8	11.9154	15.86	10.24	26.10	50.00	-23.90	AVG	P

4.2 Telecommunication ports Conducted Emission Test

4.2.1 Schematics of the test




EUT: Equipment Under Test

4.2.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer, Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



4.2.3 Telecommunication ports conducted Emission Limit

Frequency (MHz)	Class A Limits				Class B Limits			
	Quasi-peak Level		Average Level		Quasi-peak Level		Average Level	
	Voltage dB(uV)	Current dB(uA)	Voltage dB(uV)	Current dB(uA)	Voltage dB(uV)	Current dB(uA)	Voltage dB(uV)	Current dB(uA)
0.15 ~ 0.50	97 to 87	53 to 43	87 to 74	40 to 30	84 to 74	40 to 30	74 to 64	30 to 20
0.50 ~ 30.00	87	43	74	30	74	30	64	20

Notes: 1.*decreasing linearly with logarithm of frequency.
 2.The tighter limit shall apply at the transition frequencies

4.2.4 Test Results: N/A

Limits for Conducted Emission test, please refer to limit line (Quasi-peak) and Average in the following diagram labelled as (QP)&AV

Remark:

Calculated measurement uncertainty=1.9dB

A: Conducted Emission on Telecommunication port (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 75 %RH Atmospheric Pressure: 101 kPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: N/A

Please refer to following diagram for individual

Frequency (MHz)	Port	Reading(dBμV)		Limit(dBμV)	
		Quasi-peak	Average	Quasi-peak	Average

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



B: Conducted Emission on Telecommunication port (150kHz to 30MHz)

EUT Operating Environment

Temperature: 25°C Humidity: 75 %RH Atmospheric Pressure: 101 kPa

EUT set Condition: Normal operation mode

Equipment Level: Class B

Results: N/A

Please refer to following diagram for individual

Frequency (MHz)	Port	Reading(dBμA)		Limit(dBμA)	
		Quasi-peak	Average	Quasi-peak	Average


Note: This test item is not applicable because there is no telecommunication port

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



4.3 Radiated Disturbance Test


4.3.1 Schematics of the test



4.3.2 Test Method:

The test was performed in accordance with EN 55032:2015+A11:2020+A1:2020

Block diagram of Test setup



4.3.3 Radiated Disturbance Test Limit

Frequency Range (MHz)	Quasi-Peak limits (dB μ V/m)	
	Class A Limits	Class B Limits

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer, Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



30-230	50.00	40.0
230-1000	57.00	47.00
1000-3000	56(AV)/76(PK)	50(AV)/70(PK)
3000-6000	60(AV)/80(PK)	54(AV)/74(PK)

Note: The lower limit shall apply at the transition frequencies

4.3.4 Test result

Limits for Radiated Disturbance test, please refer to limit line (Quasi-peak) in the following diagram labelled as (QP)


Remark:

Calculated measurement uncertainty=4.7dB

A: Radiated Disturbance (30MHz----1000MHz)

Project Number:	CASE3	Test Time:	2024-09-13_14.00.46
EUT Name:	3-MODES 98 KEY CASKET HOT-SWAPPABLE RGB MECHANICAL	Test Engineer:	CHASE
Manufacturer:	Eastern Times Technology Co., Ltd	Test Standard:	EN 55032
Model:	K686WB-RGB-PRO	Work Addition:	Charging
Temp.(°C):	25	Load:	
Hum.:	65%	Test Voltage:	230V~, 50Hz

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




No	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	45.516	23.42	-11.39	40.0	16.58	Peak	210.00	100	Horizontal	Pass
2	101.520	22.03	-13.44	40.0	17.97	Peak	323.00	100	Horizontal	Pass
3	166.736	23.23	-16.06	40.0	16.77	Peak	75.00	100	Horizontal	Pass
4	262.014	24.66	-11.90	47.0	22.34	Peak	325.00	100	Horizontal	Pass
5	428.328	27.37	-8.07	47.0	19.63	Peak	190.00	100	Horizontal	Pass
6	666.161	31.10	-4.50	47.0	15.90	Peak	52.00	100	Horizontal	Pass

B: Radiated Disturbance (30MHz----1000MHz)

Project Number:	CASE3	Test Time:	2024-09-13_14.02.27
EUT Name:	3-MODES 98 KEY CASKET HOT-SWAPPABLE RGB MECHANICAL	Test Engineer:	CHASE
Manufacturer:	Eastern Times Technology Co., Ltd	Test Standard:	EN 55032
Model:	K686WB-RGB-PRO	Work Addition:	Charging
Temp.(°C):	25	Load:	
Hum.:	65%	Test Voltage:	230V~, 50Hz

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	45.274	31.14	-11.40	40.0	8.86	Peak	280.00	100	Vertical	Pass
2	63.942	23.66	-13.32	40.0	16.34	Peak	358.00	100	Vertical	Pass
3	119.703	21.78	-15.26	40.0	18.22	Peak	38.00	100	Vertical	Pass
4	162.372	29.58	-16.39	40.0	10.42	Peak	88.00	100	Vertical	Pass
5	360.445	26.26	-9.50	47.0	20.74	Peak	289.00	100	Vertical	Pass
6	784.229	32.14	-3.08	47.0	14.86	Peak	97.00	100	Vertical	Pass

C: Radiated Disturbance (30MHz----1000MHz)

Project Number: CASE3
 EUT Name: 3-MODES 98 KEY CASKET
 HOT-SWAPPABLE RGB MECHANICAL
 Manufacturer: Eastern Times Technology Co., Ltd
 Model: K686WB-RGB-PRO
 Temp.(°C): 25
 Hum.: 65%

Test Time: 2024-09-13_14.10.13
 Test Engineer: CHASE
 Test Standard: EN 55032
 Work Addition: Wired Operation Mode
 Load:
 Test Voltage: DC5.0V

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




No.	Frequency (MHz)	Results (dBuV/m)	actor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	43.819	32.87	-11.48	40.0	7.13	Peak	331.00	100	Horizontal	Pass
2	53.274	33.56	-11.51	40.0	6.44	Peak	329.00	100	Horizontal	Pass
3	162.614	33.75	-16.38	40.0	6.25	Peak	287.00	100	Horizontal	Pass
4	180.070	35.35	-15.31	40.0	4.65	Peak	258.00	100	Horizontal	Pass
5	341.292	31.83	-9.73	47.0	15.17	Peak	24.00	100	Horizontal	Pass
6	461.300	40.59	-7.84	47.0	6.41	Peak	169.00	100	Horizontal	Pass

D: Radiated Disturbance (30MHz----1000MHz)

Project Number:	CASE3	Test Time:	2024-09-13_14.08.32
EUT Name:	3-MODES 98 KEY CASKET HOT-SWAPPABLE RGB MECHANICAL	Test Engineer:	CHASE
Manufacturer:	Eastern Times Technology Co., Ltd	Test Standard:	EN 55032
Model:	K686WB-RGB-PRO	Work Addition:	Wired Operation Mode
Temp.(°C):	25	Load:	
Hum.:	65%	Test Voltage:	DC5.0V

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1*	41.311	38.28	-11.91	40.0	1.72	QP	287.00	101	Vertical	Pass
2*	42.768	34.91	-11.55	40.0	5.09	QP	264.00	102	Vertical	Pass
3	53.517	35.23	-11.52	40.0	4.77	Peak	281.00	100	Vertical	Pass
4	163.099	36.96	-16.36	40.0	3.04	Peak	194.00	100	Vertical	Pass
5	449.663	41.11	-8.01	47.0	5.89	Peak	166.00	100	Vertical	Pass
6	829.565	38.00	-2.89	47.0	9.00	Peak	328.00	100	Vertical	Pass

4.4 Harmonic Current Emission Test

4.4.1 Schematic of the test

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




EUT: Equipment Under Test

4.4.2 Test Method:

The test was performed in accordance with EN IEC 61000-3-2:2019 +A1:2021

Block diagram of Test setup



4.4.3 Limits of Harmonic Current Emission For Class A

Harmonic order n	Maximum permissible harmonic current A
Odd harmonics	
3	2,30
5	1,14
7	0,77
9	0,40
11	0,33
13	0,21
$15 \leq n \leq 39$	$0,15 \frac{15}{n}$
Even harmonics	
2	1,08
4	0,43
6	0,30
$8 \leq n \leq 40$	$0,23 \frac{8}{n}$

4.4.4 Test Results

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Please refer to the following pages

Harmonic Current Emission Test

EUT Operating Environment

Temperature: 25°C Humidity: 53%RH Atmospheric Pressure: 101 kPa

EUT set Condition:

Results: N/A

N/A ---the input power less than 75W.


Please refer to following diagram for individual

Harmonic results as a% of the limits

No	(Test result/Limit) %						
1		11		21		31	
2		12		22		32	
3		13		23		33	
4		14		24		34	
5		15		25		35	
6		16		26		36	
7		17		27		37	
8		18		28		38	
9		19		29		39	
10		20		30		40	

4.5 Voltage Fluctuations & Flicker Test

4.5.1 Schematic of the test




EUT: Equipment Under Test

4.5.2 Test Method:

The test was performed in accordance with EN 61000-3-3:2013+A2:2021+AC:2022-01

Block diagram of Test setup

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



4.5.3 Test Results


Result: N/A

5.0 Immunity Test

5.1 Electrostatic Discharge

5.1.1 Schematic of the test

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.1.2 Test method

The test was performed in accordance with EN 61000-4-2: 2009

5.1.3 Test severity

- ± 4kV for direct & in-direct Contact Discharge
- ± 8kV for air Discharge

Performance Criterion Require: **B** (Please see following table)

5.1.4 Susceptibility performance Criteria and Severity level

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Level	Test Voltage Direct & in-direct contact Discharge (kV)	Test Voltage Air discharge(kV)
1	± 2kV	± 2kV
2	± 4kV	± 4kV
3	± 6kV	± 8kV
4	± 8kV	± 15kV

5.1.5 Test Result

EUT Operating Environment

Temperature: 25°C Humidity: 53%RH Atmospheric Pressure: 101 kPa

The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Please refer to the following table for individual results.

Location	Discharge Method	Test Voltage	Results
HCP (Horizontal coupling plane)	In-Direct	± 2kV, ± 4kV	Pass
VCP (Vertical Coupling Plane)	In-Direct	± 2kV, ± 4kV	Pass
Type-C Port	Contact Discharge	± 2kV, ± 4kV	Pass
Screw	Contact Discharge	± 2kV, ± 4kV	Pass
Enclosure	Air Discharge	± 2kV, ± 4kV, ± 8kV	Pass
Keys	Air Discharge	± 2kV, ± 4kV, ± 8kV	Pass
Switch	Air Discharge	± 2kV, ± 4kV, ± 8kV	Pass
Indicator Light	Air Discharge	± 2kV, ± 4kV, ± 8kV	Pass
Gaps	Air Discharge	± 2kV, ± 4kV, ± 8kV	Pass

Remark: Calculated measurement uncertainty= 0.2kV


5.2 RF field strength susceptibility (80MHz-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz)

5.2.1 Schematics of the test

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.2.2 Test Method:


The test was performed in accordance with EN IEC 61000-4-3:2020

Severity: Level 2 (3V/m)

Modulation: 80% AM

Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.2.3 Susceptibility performance Criteria and severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Level	Field Strength (V/m)
1	1
2	3
3	10

5.2.4 Test Result:

EUT Operating Environment

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Frequency (MHz)	Face	Polarity	Level (V/m)	Dwell Time(s)	Sweep Rate (%)	Results
80-1000	0 °	Horizontal	3	1	1	Pass
80-1000	90 °	Horizontal	3	1	1	Pass
80-1000	180 °	Horizontal	3	1	1	Pass
80-1000	270 °	Horizontal	3	1	1	Pass
80-1000	0 °	Vertical	3	1	1	Pass
80-1000	90 °	Vertical	3	1	1	Pass
80-1000	180 °	Vertical	3	1	1	Pass
80-1000	270 °	Vertical	3	1	1	Pass
1800, 2600, 3500, 5000	0 °	Horizontal	3	1	1	Pass
	90 °	Horizontal	3	1	1	Pass
	180 °	Horizontal	3	1	1	Pass
	270 °	Horizontal	3	1	1	Pass
1800, 2600, 3500, 5000	0 °	Vertical	3	1	1	Pass
	90 °	Vertical	3	1	1	Pass
	180 °	Vertical	3	1	1	Pass
	270 °	Vertical	3	1	1	Pass


5.3 Electrical Fast Transient/Burst (EFT/B) immunity test

5.3.1 Schematics of the test

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.3.2 Test Method

The test was performed in accordance with EN 61000-4-4:2012
 Severity: Level 2 (1kV)
 Performance Criterion Require: **B** (Please see following table)

Block diagram of Test setup



5.3.3 Susceptibility performance Criteria and Severity Level

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Level	Open Circuit output Test Voltage ± 10%	
	On power Supply Lines	On I/O (Input/output) Signal data and control lines
1	0.5kV	0.5kV
2	1kV	1kV
3	2kV	2kV
4	4kV	4kV
X	Special	Special

5.3.4 Test Results

EUT Operating Environment

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Inject location: AC mains

Inject Line	Voltage kV	Inject Times (s)	Method	Results
L	± 1	120	Direct	Pass
N	± 1	120	Direct	Pass
L-N	± 1	120	Direct	Pass


5.4 Surge test

5.4.1 Schematics of the test

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




5.4.2 Test Method:

The test was performed in accordance with EN 61000-4-5:2014

Severity: Level 2 (Line to Neutral at 1kV)

Performance Criterion Require: B (Please see following table)

Block diagram of Test setup



5.4.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Severity Level	Open-Circuit Test Voltage
----------------	---------------------------

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



	kV
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

5.4.4 Test Results

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Test location:

Location	Polarity	Phase Angle	No of Pulse	Pulse Voltage(kV)	Results
L-N	+	90	5	1.0	Pass
	-	270	5	1.0	Pass


5.5 Conducted Immunity test

5.5.1 Schematics of the test

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.5.2 Test Method

The test was performed in accordance with EN 61000-4-6:2014
 Severity: Level 2 (3 V rms),0.15MHz—80MHz
 Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.5.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Severity Level	Voltage Level (e.m.f) V
1	1
2	3
3	10
*	Special

5.5.4 Test Results:

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

Please refer to the following table for individual results.

Frequency Range (MHz)	Injected Position	Strength	Criterion	Result
0.15 - 10	C Line	3V (rms)	A	Pass
10 - 30	AC Line	3 to 1V (rms)	A	Pass
30 - 80	AC Line	1V (rms)	A	Pass

Note: the amplitude of a test level varies over a given frequency range, it changes linearly with respect to the logarithm of the frequency

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.6 Power-Frequency magnetic field test

5.6.1 Schematics of the test




5.6.2 Test Method

The test was performed in accordance with EN 61000-4-8:2010

Severity: Level 1 (1A/m),

Performance Criterion Require: A (Please see following table)

Block diagram of Test setup



5.6.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

Severity Level

Severity Level	Magnetic Field Strength A/m
1	1
2	3
3	10
4	30
5	100
*	Special

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.6.4 Test Results:

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Test Level	Testing Duration	Coil Orientation	Criterion	Result
1A/m	5 Mins	X	A	N/A
1A/m	5 Mins	Y	A	N/A
1A/m	5 Mins	Z	A	N/A

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



5.7 Voltage Dips/Interruptions immunity test

5.7.1 Schematics of the test




5.7.2 Test Method:

The test was performed in accordance with EN IEC 61000-4-11: 2020

Performance Criterion Require: C&B (Please see following table)

Block diagram of Test setup



5.7.3 Susceptibility performance Criteria and Severity Level

Susceptibility performance Criteria

Criterion	Description
A	No change in operational mode or degradation of performance outside of specification and no change in stored parameters.
B	Degradation of performance allowed during the test the EUT returning to intended operation after the test.
C	Loss of function allowed during the test, provided that function is self recoverable or can be recovered by operation of controls.

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Severity Level

Voltage Dip	Test Level %Ut	Reduction	Duration (Periods)	Performance Criteria
	<5	>95	0.5	B
	70	30	25	C
Voltage Interceptions	Test Level %Ut	Reduction	Duration (Periods)	Performance Criteria
	<5	>95	250	C

5.7.4 Test Result:

EUT Operating Environment

Temperature: 25°C Humidity: 75%RH Atmospheric Pressure: 101 kPa

Please refer to the following table for individual results.

Voltage Dip:

Test Level % Ut	Reduction	Duration (periods)	Phase Angle	Meet Criterion	Result
0	100	0.5	0 ° - 360 °	B	Pass
70	30	25	0 ° - 360 °	B	Pass

Voltage Interceptions:

Test Level % Ut	Reduction	Duration (periods)	Phase Angle	Meet Criterion	Result
0	100	250	0 ° - 360 °	B	Pass

The report refers only to the sample tested and does not apply to the bulk.
 This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
 In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



6.0 Product Labelling

6.1 CE Mark label specification

Text of the mark is black or white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing and shall be affixed at a conspicuous location on the EUT or silk-screened onto the EUT.



6.2 Mark Location: Rear enclosure

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Appendix:

Conducted Emissions



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it, or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES, to his customer, supplier or other persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES, will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report, the SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Radiated Emissions



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Outside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Outside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Outside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Outside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Inside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Inside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk. This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report. In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Inside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it or a certified copy thereof prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.




Inside View-Keyboard



The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



Inside View-Keyboard



--End of the Report--

The report refers only to the sample tested and does not apply to the bulk.
This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for advertising. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.
In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.